



	SBC-25B	SBC-50B	SBC-65B	SBC-95B
<b>Lids</b>	1	2	2	3
<b>Exterior Dimensions (L x D x H)</b>	26 <sup>3</sup> / <sub>8</sub> x 26 <sup>5</sup> / <sub>8</sub> x 34 <sup>1</sup> / <sub>4</sub>	49 <sup>1</sup> / <sub>2</sub> x 26 <sup>5</sup> / <sub>8</sub> x 34 <sup>1</sup> / <sub>4</sub>	64 <sup>1</sup> / <sub>2</sub> x 26 <sup>5</sup> / <sub>8</sub> x 34 <sup>1</sup> / <sub>4</sub>	95 <sup>1</sup> / <sub>4</sub> x 26 <sup>5</sup> / <sub>8</sub> x 34 <sup>1</sup> / <sub>4</sub>
<b>Capacity</b>				
12 oz. Bottles	4.5 cases	16.5 cases	22 cases	37.5 cases
12 oz. Cans	6 cases	24 cases	32 cases	55 cases
<b>HP</b>	1/6	1/4	1/3+	1/2+
<b>Voltage</b>	115/60/1	115/60/1	115/60/1	115/60/1
<b>Amps</b>	1.42	8	8.5	9.6
<b>Nema Config</b>	5-15P	5-15P	5-15P	5-15P
<b>Crated/Uncrated Weight</b>	172/139 lb	299/244 lb	350/275 lb	451/363 lb

- Exteriors include attractive wear-resistant vinyl on steel in black finish with stainless steel top
- Interior: 304 stainless steel floors with smooth white finish on interior sides
- Standard removable bottle cap opener and cap catcher
- Aluminum coated interior metal and epoxy coated steel wire adjustable dividers
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- Guided airflow cools bottles on top first
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Condensing units slides out for easy maintenance

\* Specifications subject to change without notice

