

FRY TOP S Electric M40 AISI Plate - Rigato - Thermostat Top Version

Project:
Rev.:
Zone:
Location:



CODICE
CR1651139

MODELLO
D72/10TSFTEAR

SERIE
DIAMANTE70



GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200 Wide range of accessories.

TECHNICAL SPECIFICATIONS

15 mm thick cooking plate totally independent of the hob .
Large floodable channel around the perimeter of the hotplate for collecting cooking residues, sloping towards the front for draining liquids into the large drawer.
Large grease collection drawer.
Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen.
Plate not welded to the machine bed with optimisation of structural points under thermal stress
Stainless steel overflow plug, supplied as an accessory, for channel flooding management
Non-welded plate for fast maintenance and replacement in the utility
New version with identical cooking surface area and reduced energy output. An increase in output per cm² allows a reduction in consumption of up to 15% compared to conventional versions
Tubular burner with self-stabilising flame with great uniformity of heat distribution.

Floodable gutter for collecting cooking residues around the perimeter of the cooking plate easier cleaning and better retention of moisture in cooking food
Capacious grease collection drawer with capacity for the entire volume of the perimeter channel
Grooved plate design ensures cleanliness right to the end of the plate
Non-welded plate for fast maintenance and replacement in the utility
Plate not welded to the machine bed with optimisation of structural points under thermal stress
Thermal cutting that facilitates the user and adjacent machinery.
Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen.
Water dispenser kit available as an accessory

FRY TOP S Electric M40 AISI Plate - Rigato - Thermostat Top Version

Project:
Rev:
Zone:
Location:



CODICE
CR1651139

MODELLO
D72/10TSFTEAR

SERIE
DIAMANTE70

Technical Information

| SPECIFICATION | DATA |
|-----------------------|--------------------------------------|
| MATERIAL | CR1651139 |
| DEFINITION | D72/10TSFTEAR FTE RIBBED 430 M40 TOP |
| COMMERCIAL LINE | DIAMANTE |
| SUPPLY | ELECTRICS |
| DIM. WIDTH | 400 mm |
| DIM. PRODUCTIVITY | 730 mm |
| DIM. HEIGHT | 250 mm |
| NET WEIGHT | 41,000 Kg |
| VOLUME (net) | 0,073 |
| PACKAGE LENGTH | 440,000 mm |
| PACKAGE WIDTH | 850 mm |
| PACKAGING HEIGHT | 550,000 mm |
| PACKAGE VOLUME | 0,206 m3 |
| GROSS PACKING WEIGHT | 47,000 Kg |
| STANDARD POWER SUPPLY | 380-415V 3N |
| FREQUENCY | 50-60 Hz |
| ELECTRICAL POWER | 3,600 kW |
| IP GRADE | IPX4 |
| CERTIFIED MODEL | D72/10TSFTEAR |

FRY TOP S Electric M40 AISI Plate - Rigato - Thermostat Top Version

Project:
Rev:
Zone:
Location:




CODICE
CR1651139

MODELLO
D72/10TSFTEAR

SERIE
DIAMANTE70

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm
MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda

| | |
|--|--|
| E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico | G Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligação gás |
| S Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água | H20 Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de agua - Wateraansluiting - Junção alimentação água |
| S1 Scarico vasca - Wannababflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba | A1 = Calda - Heiss - Warm - Chaud - Caliente - Warm - Morno A2 = Fredda - Kalt - Cold - Froid - Fria - Koude - Frio |
| S2 Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de depresión - Onderdrukklep - Válvula de depressão | |
| S3 Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de agua intersticios - Afvoer water tussenruimte - Descarga de água na marmita com Sistema de aquecimento indirecto | |
| S4 Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulação de dreno | L Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaakraan - Torneira de nivel |

FRY TOP S Electric M40 AISI Plate - Rigato - Thermostat Top Version

Project:
Rev:
Zone:
Location:



CODICE
CR1651139

MODELLO
D72/10TSFTEAR

SERIE
DIAMANTE70

Product's PLUS




Plate not welded to the machine bed with optimisation of structural points under thermal stress



Thermal cutting that facilitates the user and adjacent machinery.




Capacious grease collection drawer with capacity for the entire volume of the perimeter channel



Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen.



Grooved plate design ensures cleanliness right to the end of the plate



Water dispenser kit available as an accessory



Non-welded plate for fast maintenance and replacement in the utility

FRY TOP S Electric M40 AISI Plate - Rigato - Thermostat Top Version

Project:
Rev:
Zone:
Location:



CODICE
CR1651139

MODELLO
D72/10TSFTEAR

SERIE
DIAMANTE70



Water dispenser kit available as an accessory

FRY TOP S Electric M40 AISI Plate - Rigato - Thermostat Top Version

Project:
Rev:
Zone:
Location:



CODICE
CR1651139

MODELLO
D72/10TSFTEAR

SERIE
DIAMANTE70

ACCESSORIES

| CODE | MODELLO | DESCRIZIONE |
|-----------|----------|------------------------------|
| CR1354989 | PRPC | |
| CR1354999 | PKLR | |
| CR1356399 | RPR | Striped chrome plate scraper |
| CR1658619 | 97CPFT4 | M40 fry top cleaning drawer |
| CR1658609 | 97TFT | |
| CR1658639 | 7AFT4 | |
| 7KSCFT | 7KSCFT | |
| CR1658839 | Q794CAFT | |