







	SBB-24-48SS	SBB-24-60SS	SBB-24-72SS
Doors	2	2	3
Exterior Dimensions (L x D x H)	48 ½ x 24 ½ x 35 ½	60 % x 24 % x 35 %	72 ½ x 24 ½ x 35 ½
Capacity cu.ft.	11.8	15.8	19.6
HP	1/3	1/3	1/3
Voltage	115/60/1	115/60/1	115/60/1
Amps	6.4	6.4	7.4
Nema Config	5-15P	5-15P	5-15P
Crated/Uncrated Weight	231/216 lb	290/255 lb	352/310 lb

- All-stainless steel
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs
- Self -Closing/Lockable doors: Positive seal, self-closing door(s) to help conserve energy and security
- * Specifications subject to change without notice



