

Blixer® 5



5.5 L

A SALES FEATURES

Blixer 5 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES

Blixer 5. 3-phase. Power: 3 HP. Speeds: 1750 and 3450 rpm. 5.5 L stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Totally leakproof lid with scraper arm. 3 – 18 portions (7 oz.).

Select your options at the back page, **F** part.

C TECHNICAL DATA

| | |
|-----------------------|--|
| Output power | 3 HP |
| Electrical data | 208-240V/60/3 |
| Speeds | 1750 and 3450 rpm |
| Dimensions (WxDxH) | 11" x 14 7/16" x 19 3/8" Cube: 3.68 |
| Rate of recyclability | 95% |
| Net weight | 60 lbs |
| Nema # | L15-20P |
| Reference | BLIXER 5 - 208-240V/60/3 |

D

Number of 7 oz. portions per service



Amount processed per operation

.075 to 7 lbs

E

PRODUCT FEATURES / BENEFITS

MOTOR UNIT

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 3 HP
- Stainless-steel motor shaft
- All-metal motor base
- Magnetic safety system, thermal failsafe.
- Speeds 1750 and 3450 rpm

BLIXER® FUNCTION

- 5.5 L stainless-steel bowl with handle for better grip.
- Bowl-base blade assembly with two high-strength, stainless-steel, fine-serrated blades for homogeneous processing – even for small amounts.
- Central lid opening for adding liquid or solid ingredients during processing.
- High heat and shock-resistant see-through lid to monitor processing from start to finish.
- Leakproof lid and bowl unit with bowl scraper arm and lid wiper.
- All parts are dishwasher-safe and can easily be removed for cleaning.

STANDARD ATTACHMENTS

- 5.5 L bowl with lid.
- Bowl scraper arm and lid wiper.
- Blade assembly with two fine-serrated, stainless-steel blades and a detachable cap.

STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)



Blixer® 5

F OPTIONAL ATTACHMENTS

- Fine serrated edge stainless steel "S" blade assembly
Ref. 27155
- Coarse serrated edge stainless steel "S" blade assembly
Ref. 27180
- 5.5 L Stainless steel bowl assembly - Ref. 27165

G

ELECTRICAL DATA

208-240V/60/3 – delivered with cord and plug.

