



Patented

Fry Top with indirect heating dual control

DATASHEET

Length (mm): 1200
 Depth (mm): 700
 Height (mm): 250/460
 Net weight (kg): 145,5
 Packed unit weight (kg): 185,5
 Pallets size (mm): 1300x800x670

Electrical power (kW): 8,1 kW
 Electrical connection:
 400V 3N 50-60 Hz
 Phase: 14,54 A

Cooking surface:

- mod GE1270L2C: flat
 - mod GE1270D2C: half ribbed
 - mod GE1270T2C: ribbed
- made of stainless steel thickness 10 mm with lateral edges and scotch brite back finish.

Available cooking surface L= 1194 mm D= 595 mm
 Front dripping tray easily removable and washable
 Auto supporting structure completely made in stainless steel AISI 304, visible parts with scotch brite finish.

Adjustable plastic feet.

Heating made by resistances immersed in diathermic fluid inside a tank with expansion tank and safety valve.

Switch on/off button, cooking temperature control from 20°C to 260°C degrees by electronic thermostat.





Limit control with manual reset.

Accessories included: power cable, palette knife and kitchen scraper for cleaning.

Protection degree IPX4.





CE Certification.

GE1270L2C







E= Electrical connection

GE1270D2C



E= Electrical connection

GE1270T2C



E= Electrical connection