

## Product data sheet – Gas lava stone grill Argentina 2

MKN-No.:  
10018658

Cooking appliance according to DIN 18852 for application in the commercial preparation of food in the general catering industry, front cooking, free flow systems and snack bars. For cooking with contact heat, for frying of quick-fried pieces and for grilling meat and vegetables.



### Technical highlights

#### Material:

Casing and cover are made completely of CNS (material No. 1.4301) / AISI 304.  
Visible surfaces with polished and satin finish, 320 grit.

#### Bendings:

Cover bent downwards 30 mm at the front and bent upwards 20 mm at the rear. Designed as a drip edge at the front. 50 mm cover projection closed to the appliance body.

#### Body:

Buckling resistant, self-supporting, closed construction with side walls, rear wall and bottom.

#### Control panel:

Operation panel desk-shaped for highest ergonomic requirements and very easy cleaning. Removable from the front for easy and cost efficient service access.  
Ergonomiacally shaped knobs for a easy identification of the position.

#### Effective area:

Cast iron grate in 2 parts. Two adjustable heating zones.  
Optimized heat distribution by means of hot glowing stones underneath. Two removable fat collection containers.

#### Installation:

Equipped for installation of appliance feet which are adjustable in height (optional) or for installation on a plinth provided by customer.

#### Type of energy:

Appliance is completely tubed internally in accordance with gas requirements for the gas connection provided by customer.

#### Special feature:

#### Heating:

Heating by atmospheric linear burners, thermoelectrically protected. Piezo ignition for the ignition burners to start up the main burner.



## Product data sheet – Gas lava stone grill Argentina 2

MKN-No.:  
10018658

Cooking appliance for cooking with contact heat, for frying of quick-fried pieces and for grilling meat and vegetables.

Current drawings you will find here:  
[www.mkn.com](http://www.mkn.com)  
 ▶ Partner Login  
 ▶ spare parts database & download

### Further features

- connection, sealing by means of patented connecting method – clamp bar is rounded (R 20) at the back for easier cleaning
- manual temperature regulation by a tapswitch for each heating zone – inspection hole für ignition burner for each heating zone

### Technical data

Dimensions (LxWxH*) (mm):	800 x 700 x 700
Effective area:	2
Dim.: effect. area (LxWxH) (mm):	320 x 510 x
Diameter (mm):	
Nominal capacity (L):	
Nominal fill quantity (L):	
Connected load (electrical) (kW):	
Voltage <sup>1</sup> (V):	
Recommended fuses (A):	
Frequency range (Hz):	
Rated heat load (kW):	20
Standard gas pressure – natural gas <sup>2</sup> (mbar):	20; 25
Standard gas pressure – liquid gas <sup>2</sup> (mbar):	30; 37; 50
Gas connection:	DN 15 (1/2")
Heat-up time (Min.):	
Vapour pressure (bar):	
Refrigeration capacity (kW):	
Net weight (kg):	95
Gross weight <sup>3</sup> (kg):	106
Heat emission latent (W):	4000
Heat emission sensitive (W):	14400
Type of protection:	

\* Carcass height plus optional appliance feet with a height of 150 mm or 200 mm

### Product safety

- CE mark

### Installation requirements

- gas connection provided by customer

### Option / accessories

MKN-No.:	Description:
201517	spare lava stones, 1 set
062003	V grill grid

<sup>1</sup> special voltages on request

<sup>2</sup> further types of gas on request

<sup>3</sup> seaworthy packing on request

