



Product Code: HR200

Refrigerated Undercounter Cabinet



Features & Benefits

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate in ambient up to 40°C

External Finish		Internal Finish		Shelving			
s/s ext	Standard	aluminium	Standard	Nylon Coated Shelf	Optional		
Base Fittings		Doors		Refrigeration			
Castors - Rear Fixed	Standard	Solid	Standard	R290 - Energy Efficient	Standard		
Levelling Bolts	Standard	Specification Dimensions (Width) 684 Dimensions (Height) 824 Dimensions (Depth) 755 Weight (Unpacked, kg) 84 Weight (Packed, kg) 94.1 Gross Volume 200 Noise DbA @ 1M 69.8		R134a - Industry Standard	Optional		
Electrical, Service & Ecodesign Data				Integral Refrigeration System	Standard		
230/50/1	Standard						
Fuse Required	13						
Global Warming Potential	3						
Energy Efficiency Index	45.96						
Refrigerant Charge	0.140						
kWh (24 hours)	2.57						

Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for airflow, ensure that 25mm clearance is allowed above the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet



Application

This appliance is intended for use in ambient temperatures up to 40°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care