

ELECTRIC MANUAL BRAISING PANEL 80 lt. WITH STAINLESS STEEL BOTTOM

Project:
Rev.:
Zone:
Location:



CODICE
CR0990759

MODELLO
D94/10KBEI

SERIE
DIAMANTE90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200. Wide range of accessories.

TECHNICAL SPECIFICATIONS

Multifunctional tilting braising pan, equipment for professional catering, suitable for cooking sauces, braises and cooking with oil. It guarantees high performance, exceptional firing uniformity. Water feed directly into the tank via standard solenoid valve, controlled by a button on the front of the equipment. Cooking temperature controlled by thermostat with adjustment from 100 to 280°C.

AISI 304 stainless steel cooking vessel, 2 mm thick.

Robust, double-walled, self-balancing lids made of stainless steel to reduce heat loss.

Cooking temperature controlled by thermostat with adjustment from 100 to 280°C. Heating via armoured incoloy heating elements.

Large-radius tilting tank.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

ELECTRIC MANUAL BRAISING PANEL 80 lt. WITH STAINLESS STEEL BOTTOM

Project:
Rev:
Zone:
Location:



CODICE
CR0990759

MODELLO
D94/10KBEI

SERIE
DIAMANTE90

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0990759
DEFINITION	D94/10 KBEI BRAISING PAN EL.80 INOX
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	145,000 Kg
VOLUME (net)	0,626
PACKAGE LENGTH	840,000 mm
PACKAGE WIDTH	1020,000 mm
PACKAGING HEIGHT	1170,000 mm
PACKAGE VOLUME	1,003 m3
GROSS PACKING WEIGHT	159,200 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	9,000 kW
IP GRADE	IPX5
CERTIFIED MODEL	D94/10 KBEI

ELECTRIC MANUAL BRAISING PANEL 80 lt. WITH STAINLESS STEEL BOTTOM

Project:
 Rev:
 Zone:
 Location:


CODICE
 CR0990759

MODELLO
 D94/10KBEI

SERIE
 DIAMANTE90


SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRIJNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm
 MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



(D) 94/10 KBE ...

(D) 96/10 KBE ...



Legenda - Legende - Key - Légende - Leyenda - Legenda

- H2O** Attacco arrivo acqua - Wasseranschluss - Water inlet
 Arrivée eau - Union de agua - Wateraansluiting
EN ISO 228-1 G 3/4
- E** Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief
 Presse étoupe de câble él. - Pisacable - Elektrische kabelwartel
- S** Scarico vasca - Wannenabflussrohr - Pan outlet
 Vidange du bac - Descarga cuba - Water toevoer

ELECTRIC MANUAL BRAISING PANEL 80 lt. WITH STAINLESS STEEL BOTTOM

Project:
Rev:
Zone:
Location:



CODICE
CR0990759

MODELLO
D94/10KBEI

SERIE
DIAMANTE90

Product's PLUS



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.



Self-balancing lids.



Large-radius tilting tank.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.



ELECTRIC MANUAL BRAISING PANEL 80 lt. WITH STAINLESS STEEL BOTTOM

Project:
Rev:
Zone:
Location:



CODICE
CR0990759

MODELLO
D94/10KBEI

SERIE
DIAMANTE90

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR0592799	ZF8	
CR0592830	ZG	
CR0592820	9ZL	
MA97432000	R	
MA97433000	RI	
CR0592869	PZM	
CR0593580	9PT	
CR0592879	KPA	
CR0592940	9CAT *	Water column for top equipment