

8-BURNER GAS COOKER ON GAS OVENS

Project:
Rev.:
Zone:
Location:



CODICE
CR0995219

MODELLO
D98/10CGG

SERIE
DIAMANTE90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200. Wide range of accessories.

TECHNICAL SPECIFICATIONS

Upper burners with stabilised flame, made of nickel-plated cast iron. Thermocouple safety valves with pilot flame.
Black acid-resistant enamelled cast iron grids with long spokes for holding small pans.
AISI304 stainless steel drip trays.
Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.
Nickel-plated cast-iron stabilised flame burners with double-crown spreader (improved performance facilitated by a flame distributed over two different sectors), Grid with long spokes to facilitate holding small pots and pans
90° venturi that prevents the nozzle from clogging and accumulating dirt.

Nickel-plated cast-iron stabilised flame burners with double-crown spreader (improved performance facilitated by a flame distributed over two different sectors), Grid with long spokes to facilitate holding small pots and pans

Removable AISI 304 stainless steel bowl for maximum hygiene.

For gas ovens, radiant plate in cast iron for even heat distribution even heat distribution, stainless steel for electric ovens. Insulated stainless steel door and inner door mounted on high-strength hinges.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

8-BURNER GAS COOKER ON GAS OVENS

Project:
Rev:
Zone:
Location:



CODICE
CR0995219

MODELLO
D98/10CGG

SERIE
DIAMANTE90

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0995219
DEFINITION	D98/10 CGG 8-BURNER GAS OVEN
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	1600 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	305,000 Kg
VOLUME (net)	1,253
PACKAGE LENGTH	1660,000 mm
PACKAGE WIDTH	1020,000 mm
PACKAGING HEIGHT	1150,000 mm
PACKAGE VOLUME	1,947 m3
GROSS PACKING WEIGHT	338,000 Kg
GAS POWER	59,40
GAS POWER (G25.3/25mbar)	53,80
N. FIRES/PLATES	OTTO FUOCHI
CERTIFIED MODEL	D98/10 CGG

8-BURNER GAS COOKER ON GAS OVENS

Project:
 Rev.:
 Zone:
 Location:

CODICE
 CR0995219

MODELLO
 D98/10CGG

SERIE
 DIAMANTE90



SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRIITNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm
 MESURES EN cm - MEDIDAS EN cm - MATEN IN cm


(D) 92/10 TCG
 (D) 92/10 TCGP
 (D) 92/10 TCG1P







(D) 98/10 TCG
 (D) 98/10 TCGP
 (D) 98/10 TCG2P



(D) 92/10 CG
 (D) 92/10 CGP
 (D) 92/10 CG1P



(D) 98/10 CG (D) 98/10 CGG (D) 98/10 CGE
 (D) 98/10 CGP (D) 98/10 CGGP (D) 98/10 CGEP
 (D) 98/10 CG2P (D) 98/10 CGG2P (D) 98/10 CGE2P



Legenda - Legende - Key - Légende - Leyenda - Legend

- E** Pressacavo entrata linea elettrica - Stopfbuchse
 Electric cable stress relief - Presse étoupe de câble él
 Pisacable - Elektrische kabelwartel
- G** Attacco arrivo gas - Gasanschluss - Gas connection
 Arrivée gaz - Union de gas - Gasaansluiting
EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)
- H2O*** Attacco arrivo acqua - Wasseranschluss - Water inlet
 Arrivée eau - Union de agua - Wateraansluiting
EN ISO 228-1 G 3/4

8-BURNER GAS COOKER ON GAS OVENS

Project:
Rev:
Zone:
Location:



CODICE
CR0995219

MODELLO
D98/10CGG

SERIE
DIAMANTE90

Product's PLUS




For gas ovens, radiant plate in cast iron for even heat distribution even heat distribution, stainless steel for electric ovens. Insulated stainless steel door and inner door mounted on high-strength hinges.



90° venturi that prevents the nozzle from clogging and accumulating dirt.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.



Nickel-plated cast-iron stabilised flame burners with double-crown spreader (improved performance facilitated by a flame distributed over two different sectors), Grid with long spokes to facilitate holding small pots and pans



Removable AISI 304 stainless steel bowl for maximum hygiene.

8-BURNER GAS COOKER ON GAS OVENS

Project:
Rev:
Zone:
Location:



CODICE
CR0995219

MODELLO
D98/10CGG

SERIE
DIAMANTE90

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
SUPBRUC	SUP BRUC	
MA97365000	GGN1/1	
MA97375000	GGN2/1	
MA97377000	BF9M-X	
MA97376900	TGN2/1	
MA97378000	BF9M-T	
CR1353839	CR1353839	
CR1353849	CR1353849	
CR0592809	ZF12	
CR0592830	ZG	
CR0592820	9ZL	
MA97432000	R	
MA97433000	RI	
CR0592869	PZM	
CR0593580	9PT	
CR0592879	KPA	
CR0592940	9CAT *	Water column for top equipment