



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-4G C CI 230V 1N 50Hz

19089851

24/01/2024

DENOMINATION:

Refrigerated counter - Concept 700 Gastronorm with 4 doors, at 50Hz.

DESCRIPTION :

- Structure built with AISI-304 stainless steel
 - 50 mm, 40 kg/m³ injected polyurethane insulation.
 - Forced draught cooling system inside the room.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
 - Easier loading and unloading thanks to its door self-closing and stay open features.
 - Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
 - Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Interior LED lighting (only for models with glass doors).
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - 10 cm high splashback.
 - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
 - Tested in climatic class IV.
- Refrigerated counters.
- Castors included.
 - UK plug included.

POSSIBLE OPTIONS :

- Stainless Backing
- Legs instead of castors
- Without splashback
- Door frame resistance
- Glass door
- Granite worktop
- Drawers [1/2] unit
- Locks
- Left group
- Without breastplate
- Without Countertop
- Panoramic aperture
- Drawers [1/3] unit
- Drawers [1/3 + 2/3] unit

POSSIBLE ACCESSORIES :


- REFRIGERATION
- ACCESSORIES
- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 12035781 GN 1/1 grid in epoxy (530x325) 4

DIMENSIONS

X Width	2242 mm	X Gross width	2365 mm
Y Depth	700 mm	Y Gross depth	825 mm
Z Height	850 mm	Z Gross height	1000 mm
Net Weight	157,0 kg	Gross Weight	166,0 kg
Net volume	1,334 m ³	Gross volume	1,941 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,224 kW
Amperage (A)	1,04 A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,436 kW
Annual elec. consumption	1096,00 kWh
Power consumption 24h	3,00 kWh
Gross internal volume	581 L
Refrigeration net.vol	285 L
Climate class	4
Cooling gas load	108,000 g
Clasif. Energy efficiency	C
Energy Efficiency Index	43,48 %
Model Type	Counter Cabinet

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Number of doors	4
Condensation system	Vent.





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-4G C CI 230V 1N 50Hz

19089851

24/01/2024

- 12037936 Guide for grill GN-1/1 - wall - 562 mm - 1 piece 16

