

# **UNDERCOUNTER FREEZER**

### VUF67HC



UNDERCOUNTER

### **EXCLUSIVE WARRANTY**

- 7 Year Parts, Labor and Compressor
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)





#### CABINET CONSTRUCTION

- · Stainless Steel Exterior (galvanized back and bottom)
- **Aluminum Interior**
- · Stainless Steel 20 Gauge Doors
- · One Piece, Snap-In Magnetic Door Gaskets
- · 6" Casters Two With Brakes
- · 8' Cord And Plug (see electrical data for details)

#### **FEATURES**

- · Full Electronic Control
- · Stay-Open Door Feature For Easy Product Loading
- · Heavy-Duty, Spring Loaded Cartridge Hinges
- · Low Profile Horizontal Door Handles
- Epoxy Coated Shelves (2 per section)

#### REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Side Mounted Refrigeration System
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- · Epoxy Coated Evaporator Coil
- Freezer Capable Of Maintaining Product Temperature -10°F



Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

#### **OPTIONS & ACCESSORIES**

- · Stainless Steel Interior
- · Stainless Steel Back
- · Door Locks
- · Door Swing Orientation (at time of order)
- · Cutting Board

- · Additional Shelves
- · Shelf Clips (set of 4)
- · Casters: 3", Roller Kit, Low Profile
- 6" Legs Or 6" Seismic Legs
- · Correctional Package

Remote Models\* (6" legs only) (refrigerant must be specified at time of order, see note on back on page)

3779 Champion Blvd, Winston-Salem, NC 27105


ph: (888) 845-9800 fax: (800) 253-5168


Rev. 7/19/24 Printed in U.S.A. APPROVAL: \_\_\_ \_\_ DATE: \_\_




## VUF67HC









We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements,  $additions \ or \ replacements \ for \ previously \ purchased \ equipment. \ Dimensional \ tolerances \ +/-\ 1/4". \ Metric \ dimensions \ (MM)$ 

#### 3" Bottom & 2" Rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	20.08	Cabinet Voltage	115/60/1	Height	38"
Width, Overall (in.)	67 1/8"	Total Amperes	6.4	Width	69"
Depth, Overall (with handle)	33 3/4"	NEMA Plug (8' cord)	5-15P	Depth	35"
Height Overall (6" casters)	34 3/8"	REFRIGERATION DATA		Crated Weight	392 lbs
Depth, Door Open 90°	55 1/4"	Condensing Unit Size, HP	3/4	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified	
Door Openings (in.)	21 5/8" x 23 5/8"	Refrigerant*	R-290		
No. Of Doors/Shelves	2/4	Capacity (BTU/HR) (100°F/-20°F)	2312		
		Heat Rejection (BTU/HR)	3468	at time of order.	
		Charge (lbs/grams/ounces)	0.165 / 75 / 2.64		

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Rev. 7/19/24 Printed in U.S.A.

