



PROJECT: _____
 ITEM # _____ QTY: _____
 MODEL # _____
 AIA # _____ SIS # _____

QUARTZ ICE MAKER

QUARTZ ICE MAKER

HEM0650A90



Features and Benefits

- New harder Quartz nugget for better dispensing and slower melt rate.
- Uses R290 for a more environmentally friendly and efficient refrigerant.
- Cools beverages faster and longer while maintaining flavors better.
- Decreased water and power usage compared to cube ice makers.
- Load monitoring system constantly checks workload on gearbox shutting down system before a problem develops and preventing costly repairs.
- Water sensor eliminates low or no water failures and operates in adverse water conditions.
- Rugged stainless-steel evaporator assembly ensures reliability.
- Maintenance-free, industrial-grade double roller bearings.
- Heavy-duty gearbox provides years of trouble-free service.
- Built-in, non-contact ice detection fail safe automatic shutoff.



ICE FORMS	
QUARTZ ICE	3/4 x 1/2 x 1/2 in.
	19 x 13 x 13 mm



BIN CHART									
Model #	B40	B42	B55	B110	B700-30	B1000-48	B1300-48	B1325-60	B1660-60
capacity	344 lbs (156 kg)	351 lbs (160 kg)	510 lbs (232 kg)	854 lbs (388 kg)	680 lbs (308 kg)	1,000 lbs (454 kg)	1,320 lbs (599 kg)	1,325 lbs (601 kg)	1,660 lbs (753 kg)
width	30 in (762 mm)	22 in (559 mm)	30 in (762 mm)	48 in (1,219 mm)	30 in (762 mm)	48 in (1,219 mm)	48 in (1,219 mm)	60 in (1,524 mm)	60 in (1,524 mm)
Kit for combining wider bins with smaller models	KBT19	KBT24	KBT19	KBT23	Kit Not Required	Kit Not Required	Kit Not Required	Kit Not Required	Kit Not Required

See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.



HEM0650A90 shown atop of bin B42 (sold separately)

Warranty

- Ice Maker: **3 years parts and labor**
- Compressor: **5 years parts**

Options & Accessories

- KGEMDISPB for ice level control for a dispenser - verify adapter with disp. manufacturer

Water Filter

- Manifold System IFQ1-FS gets replacement filter IOMQ-FS

11100 E. 45th Avenue • Denver, CO 80239

Phone: 1.866.PURE.ICE

www.iceomatic.com

Rev. 07/2026 Printed in U.S.A.

Specifications are subject to change without prior notice.




APPROVAL: _____ DATE: _____

**Ice-O-Matic**

QUARTZ ICE MAKER

HEM0650A90

Line drawing note: Numbers with quote symbol " are in inches. Numbers enclosed in [brackets] are in millimeters.

PLAN / TOP VIEW**ELEVATION / FRONT VIEW****UTILITIES / BACK VIEW****Air Cooled**

A. Ice Maker Drain, 3/4" FPT

B. Ice Maker Potable Water Inlet, 3/8" FPT

C. Electrical Connection, ϕ .875" [22.2]

SPECIFICATIONS

Model	HEM0650A90
Condensing Type	Air
Voltage/Hertz/Phase	115/60/1
Min. Circuit Amp	18.5
Max Breaker Size	25 A
kWH per 100 lbs of ice at 70°F air / 50°F water	2.9
kWH per 100 lbs of ice at 90°F air / 70°F water	3.9
BTU (approx per hour)	8190
Number of Wires	3 (including ground)
Refrigerant	R290
Refrigeration Charge	3.88 oz / 110 g

Ice Production per 24 hrs	
70° air / 50° water lbs (kg)	90° air / 70° water lbs (kg)
610 (277)	492 (223)
Water Usage gallons per 100 lbs of ice 90°F air / 70°F water	
Potable	Condenser
12	N/A

OPERATING REQUIREMENTS

	MINIMUM	MAXIMUM
Ambient Temp. Range Air	50°F (10°C)	100°F (38°C)
Water Temp	40°F (4°C)	100°F (38°C)
Water Pressure	20 PSIG (1.4 BAR)	80 PSIG (5.5 BAR)

DIMENSIONS

Unit Width	21	533
Unit Depth	24.25	616
Unit Height	27.03	687
Shipping Weight	176 lbs / 80 kg	
Shipping Dimensions (in.)	24 (W) x 27 (D) x 32 (H)	
Shipping Dimensions (mm)	610 (W) x 686 (D) x 813 (H)	

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.