

R4-1500



D	Number of meals per service	10-50 covers
	Amount processed per	0.3-2.5 kg

A SALES FEATURES

The R4-1500 table-top cutter is ideal for grinding, mincing and kneading, as well as for making mousses, emulsions and smooth stuffings. It effortlessly performs even the lengthiest task in just a few minutes, consistently producing a flawless end product.

B TECHNICAL FEATURES

R4-1500 table-top cutter. 230V/50Hz/1ph. Power: 700 W. Speed: 1,500 rpm. 4.5-l stainless-steel bowl with handle, plus bowl-base, smooth-edged, twin-blade assembly. 10-50 covers.

Select the options you want from the list in Section **F** overleaf.

C TECHNICAL DATA

Output power	700 W
Electrical data	230V/50Hz/1ph 4.8 A – plug supplied
Speed	1,500 rpm
Dimensions (WxDxH)	226 x 304 x 440 mm
Rate of recyclability	95%
Net weight	15 kg
Reference	22434

CE MARKING
EN 12100-1 and 2 - 2004, EN 60204-1 - 2006,
EN 12852, EN 60529-2000 - IP55 - IP34

E PRODUCT FEATURES / BENEFITS

MOTOR UNIT

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 700 W
- Stainless-steel motor shaft
- All-metal motor base
- Magnetic safety system, thermal failsafe and motor brake
- **Single speed 1,500 rpm**
- **Pulse function** for greater cutting precision

CUTTER FUNCTION

- **4.5-l stainless-steel cutter bowl** with handle for better grip
- **Bowl-base blade assembly** with two high-strength, stainless-steel, smooth-edged blades for homogeneous processing even for small amounts
- **Central lid opening** for adding liquid or solid ingredients during processing
- High heat- and shock-resistant **see-through lid** to monitor processing from start to finish
- All parts are dishwasher-safe and can easily be removed for cleaning

STANDARD ATTACHMENTS

- 4.5-l bowl with lid
- Blade assembly with two smooth-edged, stainless-steel blades and a detachable cap

R4-1500

F OPTIONAL ATTACHMENTS

- Coarse-serrated, twin-blade assembly for grinding and kneading – Ref. 27346
- Fine-serrated, twin-blade assembly for chopping herbs and grinding spices – Ref. 27345
- Additional smooth-edged, twin-blade assembly – Ref. 27344



Coarse-serrated



Fine-serrated

G DRAWINGS AND DIMENSIONS

230 V / 50 Hz / 1 ph – power cord and plug supplied

