



**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
MUP-11G LC C CI 230V 1N 50Hz

19089984

23/01/2024

**DENOMINATION:**

Refrigerated cabinet - Concept Monoblock Gastronorm with 1 door.

**DESCRIPTION :**

- Structure built with AISI-304 stainless steel.
  - 60 mm, 40 kg/m<sup>3</sup> injected polyurethane insulation.
  - Embedded inner tray slides. Storage trays at 24 different levels 55 mm from each other.
  - Forced draught cooling system with hermetically sealed compressor.
  - Copper piping and aluminium flaps evaporator.
  - Digital display for electronic and digital control of temperature and defrosting.
  - Opened door delay alarm.
  - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
  - Built-in drainage to get rid of waste liquids inside the unit.
  - Embedded bottom and curved panels inside for easy cleaning and maintenance.
  - Height adjustable stainless steel legs.
  - Working temperature: from 0 °C to +8 °C(refrigerators) and from -18 °C to -22 °C (freezers).
  - Tested in climatic class 4.
  - Inner LED lights with power switch (in refrigerated cabinets and now also in freezing units).
- Refrigerated cabinet
- Castors included
  - UK plug included

**POSSIBLE OPTIONS :**

- Stainless Backing
- Legs instead of castors
- Door frame resistance
- Glass door
- Opposite Opening
- Pedal
- Remote group

**POSSIBLE ACCESSORIES :**


- REFRIGERATION
- ACCESSORIES
- GASTRONORM GRIDS

**SUPPLIED ACCESSORIES:**

- 12037958 GN-2/1 GRID made in Epoxi (650x530) 3

**DIMENSIONS**

X Width	653 mm	X Gross width	730 mm
Y Depth	796 mm	Y Gross depth	860 mm
Z Height	1996 mm	Z Gross height	2017 mm
Net Weight	144,0 kg	Gross Weight	151,0 kg
Net volume	1,037 m <sup>3</sup>	Gross volume	1,266 m <sup>3</sup>



**ELECTRICITY TECHNICAL SPECIFICATIONS**

Amperage (A)	0,6 A
Electric frequency	50Hz
Electric power	0,143 kW
Voltage	230V - 1N

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-600a
----------	--------

**COLD TECHNICAL SPECIFICATIONS**

Annual elec. consumption	423,00 kWh
Clasif. Energy efficiency	B
Climate class	4
Cooling gas load	95,000 g
Energy Efficiency Index	32,11 %
Gross internal volume	572 L
Model Type	Vertical cabinet
Power consumption 24h	1,16 kWh
Refrigeration net.vol	432 L
Refrigeration power	0,274 kW

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

**OTHERS**

Condensation system	Vent.
Number of doors	1



**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
MUP-11G LC C CI 230V 1N 50Hz

19089984

23/01/2024

