



Induced Energy

CS3000GB x 3kW Drop In Twin



Product Specifications

Maximum Power	7kW
Electrical Supply	CS3000GB-1 32-amp single phase CS3000GB-2 2 x 13-amp CS3000GB-3 415V AC 50Hz 32-amp 3-phase + N&E
Cord & Plug	Cord length 1.8m 5-pin 32-amp Commando 3 phase commando plug fitted, 32-amp single phase (UK) or 2 x 13 amp mains leads. Appropriate plug for each export market.
Weight	30kg
Dimensions (mm)	435 x 720 x 173mm
Construction	Ceran top, stainless steel casing
Depth of Field	Up to 30mm
Safety Features	Pan detection; boil-dry protection; overheat prevention; clean filter warning
User Interface	Display panel: Clean filter warning; No Pan Present warning; Glass hot warning; Shutdown
Controls	2 x Ergonomically designed knobs with precise settings of 1 through 99
Installation	Installation instructions provided
Cooling Clearance	Rear to front ventilation - integral overhang at rear, with easily removed filter
Bespoke Options	Ceran top design - minimum quantity 50
Warranty	2 years parts and labour, excluding case, Ceran top
CE	Approved

Induced Energy Limited operates a continuous programme of product development and improvement. .Product specifications may therefore be subject to change.

Induced Energy Ltd, Westminster Road, Brackley, Northants. NN13 7EB
Tel: 01280 875400 Email:sales@inducedenergy.com