



Demand more. Choose Foster

# CT75 Controlled Thaw Cabinet

## CT75



### Temperature

 Blast Chiller -21/1 °C

### Dimensions (mm)

W 700 D 820  
H 2080

### Capacity

75 Chilling (Kg)

### Unpacked Weight

143 KG

### Features & Benefits

Controlled Thaw cabinets alternate between circulating gentle heat and refrigeration, via special air ducting and fans, ensuring an even, speedy and safe thaw

- Easy programme selection - menu driven dial lets you simply turn to select the programme and push to start
- Thaw food safely from -18/-21°C to +1/+4°C
- Thaw cycle takes approx 7 hours based on maximum capacity and 25mm product thickness
- Overnight storage hold facility, so thawed food is ready for use when you want to use it
- Thaw cabinets alternate between circulating gentle heat and refrigeration, ensuring even and safe thaw

| External Finish                            |                       | Doors               |          | Electrical Data & Service Information |          |
|--------------------------------------------|-----------------------|---------------------|----------|---------------------------------------|----------|
| 304 Stainless Steel                        | Standard              | Solid Full          | Standard | 230 Volts                             | Standard |
| 304 Stainless Steel Rear For Island Siting | Option                | Hinged - Right Hand | Standard | 50Hz                                  | Standard |
|                                            |                       | Hinged - Left Hand  | Option   | 60Hz                                  | Option   |
| Internal Finish                            |                       | Refrigeration       |          | 1 Phase                               | Standard |
| 304 Stainless Steel                        | Standard              | Forced Air          | Standard | Running Watts                         | 677      |
|                                            |                       | Integral            | Standard | Running Amps                          | 4.3      |
|                                            |                       | R134a               | Standard | Thermal Heat Rejection (W)            | 842      |
|                                            |                       | Drain Required?     | No       | Noise (dBa @ 1m)                      | 65       |
| Shelving                                   |                       |                     |          | Fuse Required (A)                     | 13 amp   |
| GN 2/1 Shelf                               | Quantity: 10 Standard |                     |          |                                       |          |
| Additional Shelf                           | Option                |                     |          |                                       |          |
| Base Fittings                              |                       |                     |          |                                       |          |
| 80mm Castors                               | Standard              |                     |          |                                       |          |
| 150mm Legs                                 | Option                |                     |          |                                       |          |

## Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: [sales@foster-uk.com](mailto:sales@foster-uk.com)

**FOSTER  
GREEN  
PROCUREMENT**



**Demand more. Choose Foster**