



ICE MACHINE FILTER SYSTEMS AND FILTERS

KTI-5 Ice Machine Filter System



- 5" quick-twist single-cartridge water treatment system makes changing filters easy and sanitary
- Reduces sediment down to 1 micron
- Reduces chlorine taste and odor
- Consistent protection against the precipitation and accumulation of scale and corrosion
- Reduces maintenance frequency and costs, and extends equipment life

Connection - Inlet + Outlet	3/8" FNPT
Operating Pressure Range	10-125 psi
Inlet Water Temperature Range	35° - 100°F
Shipping Weight	4 lbs
Chlorine Taste and Odor Reduction Capacity	6,000 gallons
Service Flow Rate	0.75 gpm
Sediment Reduction	1 micron

KTI-10-1 Ice Machine Filter System



- 10" quick-twist single-cartridge water treatment system makes changing filters easy and sanitary
- Reduces sediment down to 0.5 micron
- Reduces chlorine taste and odor
- Consistent protection against the precipitation and accumulation of scale and corrosion
- Reduces maintenance frequency and costs, and extends equipment life
- Built in pressure gauge that allows for visual monitoring when filter needs to be changed

Connection - Inlet + Outlet	3/8" FNPT
Operating Pressure Range	10-125 psi
Inlet Water Temperature Range	35° - 100°F
Shipping Weight	3 lbs
Chlorine Taste and Odor Reduction Capacity	15,000 gallons
Service Flow Rate	1.50 gpm
Sediment Reduction	0.5 micron

KTI-10-2 Ice Machine Filter System



- 10" quick-twist duo-cartridge water treatment system makes changing filters easy and sanitary
- Reduces sediment down to 0.5 micron
- Reduces chlorine taste and odor
- Consistent protection against the precipitation and accumulation of scale and corrosion
- Reduces maintenance frequency and costs, and extends equipment life
- Built in pressure gauge that allows for visual monitoring when filter needs to be changed

Connection - Inlet + Outlet	3/8" FNPT
Operating Pressure Range	10-125 psi
Inlet Water Temperature Range	35° - 100°F
Shipping Weight	7 lbs
Chlorine Taste and Odor Reduction Capacity	30,000 gallons
Service Flow Rate	3.0 gpm
Sediment Reduction	0.5 micron

KCT-Q5 Filter



- 5" quick-twist cartridge
- Reduces sediment down to 1 micron
- Reduces chlorine taste and odor and protects against corrosive chlorine
- Consistent protection against the precipitation and accumulation of scale and corrosion
- Reduces maintenance frequency and costs, and extends equipment life
- Scale inhibition on the KCT-Q5 reduces maintenance frequency and costs and extends the equipment life

Operating Pressure Range	10-125 psi
Inlet Water Temperature Range	35° - 100°F
Shipping Weight	2 lbs
Chlorine Taste and Odor Reduction Capacity	6,000 gallons
Service Flow Rate	0.75 gpm
Sediment Reduction	1 micron



844-218-8477 TOLL FREE: 844-218-8477 FAX: 786-661-4100
12000 BISCAYNE BLVD, SUITE #108, MIAMI, FL, USA 33181
MVPGROUPCORP.COM SALES@MVPGROUPCORP.COM

514-737-9701 TOLL FREE: 888-275-4538 FAX: 877-453-8832
5659 ROYALMOUNT AVE, MONTREAL, QC, CANADA H4P2P9
MVPGROUPCORP.COM SALES@MVPGROUPCORP.COM



ICE MACHINE FILTER SYSTEMS AND FILTERS

KCT-Q10 Filter



- 10" quick-twist cartridge
- Reduces sediment down to 0.5 micron
- Reduces chlorine taste and odor and protects against corrosive chlorine
- Consistent protection against the precipitation and accumulation of scale and corrosion
- Reduces maintenance frequency and costs, and extends equipment life
- Scale inhibition on the KCT-Q10 reduces maintenance frequency and costs and extends the equipment life

Operating Pressure Range	10-125 psi
Inlet Water Temperature Range	35° - 100°F
Shipping Weight	3 lbs
Chlorine Taste and Odor Reduction Capacity	15,000 gallons
Service Flow Rate	1.5 gpm
Sediment Reduction	0.5 micron

141-0812



- Sanitary and convenience quick to change
- Reduces chlorine taste and odor and protects against corrosive chlorine
- Reduces an organic compounds (VOCs) and Trihalomethane (THM)
- Reduces maintenance frequency and costs, and extends equipment life

Operating Pressure Range	10-125 psi
Inlet Water Temperature Range	40° - 100°F
Shipping Weight	0.6 lbs
Chlorine Taste and Odor Reduction Capacity	396 gallons
Service Flow Rate	0.5 gpm
Sediment Reduction	0.5 micron

Ice Type	Models	Water Filters Systems			Filter (to be replace every 6 months)		
		KTI-5	KTI-10-1	KTI-10-2	KCT-Q5	KCT-Q10	141-0812
Bell-Gourmet	KOU-70-AB	x			x		
	KRU-70-AB	x			x		
	KCU-80-AB	x			x		
Full-Cube	KCU-110-AH						x
Half-Cube	KCU-180-AH	x			x		
	KCU-250-AH	x			x		
	KCM-450-AH		x			x	
	KCM-450-AH-22		x			x	
	KCM-670-AH		x			x	
	KCM-1100-AH			x			

****Allow 3" of clearance below unit for easy filter replacement**

Warranty:

When you buy a new Kool-it ice machine with the identified filter system, and follow the prescribed replacement schedule, MVP will extend your evaporator plate warranty by one year

New ice maker and filter system must be purchased and installed at the same time (Proof of purchase is required)

Water filters must be changed every 6 months

Must follow installation guidelines. Cannot exceed the specifications in pressure and temperatures indicated



786-600-4687
 844-218-8477
 786-661-4100
 12000 BISCAYNE BLVD, SUITE #108, MIAMI, FL, USA 33181
 MVPGROUPCORP.COM SALES@MVPGROUPCORP.COM

514-737-9701
 888-275-4538
 877-453-8832
 5659 ROYALMOUNT AVE, MONTREAL, QC, CANADA H4P2P9
 MVPGROUPCORP.COM SALES@MVPGROUPCORP.COM