

opening the door. Our NSF-listed panel meters offer an easy solution to reading internal air temperatures perfect for cases, freezers and more. Our digital panel meters are suitable for a wide range of applications.



SP160
Rectangular Solar
-58° to 158°F (-50° to 70°C)
±1°F (0.5°C) from 32° to 122°F (0 to 50°C) ±2°F from -4° to 32°F (-20° to 50°C) ±3.6°F/2°C <-4°F (-20°C) and > 122°F (50°C)
0.1°
0° to 120°F up to 90% non-condensing
10 second updates
1.4" x 0.5" (36 mm x 13 mm)
48" (1.2 m)
ABS
4.5" x 1.125" x .625" (114 mm x 29 mm x 16 mm)
Solar w/ battery back-up (1) 1.5V AAA
Hangs
3 oz (85 g)
CE RoHS
1 year

	T158	TRH122M	TRH158-0
	Digital w/ Remote Sensor	Mini Thermometer Hygrometer	Min/Max Thermometer Hygrometer
Temperature Range:	(Internal) 32° to 122°F (0° to 50°C) (External) -58° to 158°F (-50° to 70°C)	14° to 122°F (-10° to 50°C)	32° to 122°F (0° to 50°C)
Accuracy:	±2°F (±1°C)	±2°F (±1°C)	±2°F (±1°C) ±5% RH
Humidity:		10% to 99% RH	25% to 90% RH
RH Accuracy:	-	±5% from 25% to 95% RH	±5%
Unit Dimensions:	5" x 1.5" x 3.5" (127 mm x 38mm x 89mm)	2.75" x .75" x 4.25" (17 mm x 19mm x 108mm)	5" x .875" x 3.5" (127 mm x 22mm x 89mm)
Resolution:	-	0.1°	0.1°/1.0%RH
Display - LCD	2.875" x 2.125" (73 mm x 54 mm)	1.5" x 0.5" (38 mm x 13 mm)	2.875" x 2.125" (73 mm x 54 mm)
Power:	(1) 1.5V Battery AAA	(1) 1.5V Battery AAA	(1) 1.5V Battery AAA
Mounting:	Hangs or Stands	Hangs	Hangs or Stands
Weight:	5.5 oz (156 g)	3 oz (85 g)	4.5 oz (127 g)
Regulatory Listings:	CE RoHS	CE RoHS	CE RoHS
Warranty:	1 Year	1 Year	1 Year