

SUSHI DISPLAY CASE WITH LED LIGHTING, RIGHT-SIDED HNC-150BE-R-BLH

Product series:

Item number: S054-C174



This Hoshizaki HNC-150BE-R-BLH is a Sushi display case with LED lighting, right-sided. Our line of refrigerated display cases combines innovative features with a modern and elegant design, and are configured to highlight and preserve the freshness of even the most delicate fish types.

The range is designed to maintain the most natural level of humidity and food-safe temperatures, even during peak serving times with frequent door openings. The Hoshizaki refrigerated showcases assure the most natural level of humidity and food-safe temperature over their entire period of operation of the refrigeration system.

Airflow

The airflow created by the refrigeration effect of the evaporator is smooth and diffused, without forced air-circulation, which would cause dehydration and weight loss, resulting in swift deterioration of the fish or other perishable displayed food.

Temperature Control

One of the strikingly simple solutions for easy and fast temperature control: Turning the tray upside down means the food will have less contact with the cold tray and is more exposed to the air inside the sushi case. This way the cooling impact is reduced. A thermometer inside the cabinet helps you to monitor the inside temperature at all times.

Attractive Display

The tubular-shaped evaporator absorbs the heat continuously. Condensation freezes on its external surface, maintaining an attractive frost layer with no dripping. This model is equipped with LED lighting that can be turned on and off as needed.

Convenience

The practical anti-slip top is ideal to place serving dishes. The condensing unit of all our models sits either on the right- or left-hand side, with the outflow of air positioned on the sides away from the operator.

Easy Cleaning

The sliding door with 150 mm height and the lightweight ABS trays with a wave-shaped profile are easily disassembled and removed for daily cleaning.

SPECIFICATIONS

Product title	Sushi display case with LED lighting, right-sided
Temperature (°C) approx.	5
Electric connection	1/220 - 240V/50Hz
Dimensions W x D x H (mm)	1500 x 345 x 270
Refrigerant	R600a

Net capacity (l)	57
Net weight (kg)	37
Gross Weight Packed (kg)	52
Electric consumption (kW)	0.145
Electric connection	1/220 - 240V/50Hz