

breite\_  
0.pdf



# MRFvd 4011

## Performance

LED

<b>Gross capacity</b>	400 litre
<b>Ext. dimensions in mm (w/d/h)</b>	597/654/1884
<b>Int. dimensions in mm (w/d/h)</b>	475/423/1659
<b>Energy efficiency class</b>	
Energy consumption in 365 days	566.03 kWh
Climate rating/Temperature class	CC2 / K4
Ambient temperature range	+10°C to +40°C <sup>1</sup>
Refrigerant	R 600a
Noise output	50 dB(A)
Connection Rating	2.0 A
Frequency/voltage	50 Hz / 220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+1°C to +15°C
Housing material/colour	steel/grey
Door material	Insulated glazed door
Liner Material	moulded polystyrol white
Type of Control	analogue controls
Temperature display	external digital
Interior light	LED
Adjustable Shelving	5
Loading capacity 0.5L PET/facings 0.5L PET	253/7
Loading capacity 0.33L can/facings 0.33L can	506/7
Shelf loading	45 kg
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation	50/45 mm
Gross/net weight	84/79 kg
EAN-Nr.	9005382232439

<sup>1</sup> Indicates the ambient temperature at which the device can be operated safely.