



SLICER GSM-300 230/50/1 UK

Ø 300 mm blade.



5051075

SPECIFICATIONS



Blade diameter: 300 mm
Cutting capacity: 210 mm x 220 mm
Slice thickness: 0 mm - 16 mm
Carriage run: 440 mm
Total loading: 246 W
IP Protection grade: IP-X1
Electrical supply: 230 V / 50 Hz / 1~
Plug: UK

External dimensions (W x D x H)

- ✓ Width: 650 mm
- ✓ Depth: 430 mm
- ✓ Height: 440 mm

Net weight: 19 kg

Crated dimensions

485 x 530 x 630 mm
Gross weight: 25 kg

SALES DESCRIPTION

Belt driven slicer.

- ✓ Slicer made of a special anodized aluminum alloy, hygienic, and anticorrosive.
- ✓ Professional slicer with blade protective ring and carriage lock.
- ✓ High-powered ventilated motor.
- ✓ Easy-to-mount sharpener.
- ✓ Decimal thickness adjustment from 0 to 16 mm.
- ✓ Plate mounted on self-lubricating bushings and bearings.
- ✓ Easy cleaning, no need for tools. Dishwasher-safe detachable grip points.
- ✓ Luminous double on/off 24V switch.
- ✓ Safety print.

INCLUDES

- ✓ Blade removal tool.



www.sammic.co.uk

Food Service Equipment Manufacturer

Unit 2, Trevanth Road
Troon Industrial Park
LE4 9LS - Leicester

uksales@sammic.com
Tel.: +44 0116 246 1900



Project

Date

Item

Qty

Approved

product sheet
updated 25/01/2024