Oasis

Combination Non-Refrigerated Service Above Refrigerated Self-Service Case

Structural Concepts®
DELIVERING FRESH. ALWAYS.™

• **COU2757R** 27-1/2"L x 34-3/4"D x 57-3/4"H



COU2757R

Included

- Breeze self-contained refrigeration
- Angled deck (n/a w/display steps)
- Casters
- Clear glass shelves, lighted (LED 3500K)
- Condensate pan (self-contained refrig. only)
- Curved single pane, fixed front glass
- Full end panel w/mirror interior
- LED 3500K top & shelf lights
- One year parts & labor; 5 year compressor warranty
- Warmest average product temperature of 40°F or less

Specify	Standard Features	Additional Options
EXTERIOR COLOR	• Laminate (stock colors)	• Laminate (non-stock colors) • Stainless steel
INTERIOR COLOR	• Powder coated Silversan Black	• Stainless steel
REAR DOORS	• Clear glass rear sliding doors w/o lock	• Reflective glass rear sliding doors w/o lock
ELECTRICAL CONNECTION	• 6' Straight blade power cord (self-cont.)	• 6' Locking power cord (self-cont.)
MISCELLANEOUS		• Rear door lock • Second year parts & labor warranty (excludes compressor)
ACCESSORIES		• 2"H Display steps • Night curtain, retractable, non-locking • Removable wire security cover, locking


Oasis

Combination Non-Refrigerated Service Above Refrigerated Self-Service Case

Structural Concepts
DELIVERING FRESH. ALWAYS.™


Intended Environment:	Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.	
Zone	**Intended Product To Be Displayed**	**Warmest Avg Prod Temp ° F**
1	Packaged refrigerated products	40
2	Packaged non-refrigerated products	Ambient

PLAN VIEW



NO SELF-CONTAINED ACCESS WITHOUT PULLING OUT CONDENSER

SIDE VIEW



NOTE: ALL DIMENSIONS APPROXIMATE

ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).
LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH ¾" OR 1½" PVC TUBE).
REFRIGERATION LINE CONNECTION.
REMOTE FLOOR SINK & UTILITIES ACCESS AREA.
SELF-CONTAINED CASE SERVICE ACCESS AREA.
DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications

Model	L"	L1"	L2"	System Circuit Volts			Phs	Freq	Amps ***	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt
COU2757R	26.00	27.50	.00	Self-Contained (R290)	Circuit #1	110-120	1	60	10.43	965	2+G	5-15P or L5-15P	N/A	N/A	N/A	800

*** Does not include electric defrost on freezer models.

Regulatory Approvals:	
All Models	Accordance with AHRI Std 1200 ETL Listed to UL 60335-2-89 ETL Listed to CAN/CSA 22.2 No. 120 ETL Sanitation to NSF/ANSI 7

In Accordance with AHRI Std 1200

DOE 2017 Energy Efficiency Compliant

Important Notes:

1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle
2) 35 1/2" Minimum door entry clearance required (Without shipping skid).
3) Compressor air intake from rear and out front panel at toe kick. Front panel cannot be blocked. Product must be cooled before being displayed within the case.

⚠ **WARNING:** This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Placement of Case

Consider where the display case will be positioned relative to walls, ceilings, HVAC vents, windows, and other equipment discharging warm air.

The 5′ - 10′ - 15′ Rule

Stay 5′ away from an exterior window

Direct sunlight increases the heat load on the front of the display resulting in the refrigeration system having to work harder and possible condensation on the case.

Remain 10′ away from HVAC ceiling vents

Air blowing on the front of the display interrupts the air curtain and causes product temperatures to increase.

Minimum 4″ clearance to walls & ceilings.
Refer to spec sheets & design guide for further information.

With service display cases that have a glass front, air blowing on the front glass causes condensation to develop.

Position the display 15′ away from exterior doors

Air drafts from the front exterior doors interrupt the air curtain, allowing warm air to penetrate the inside of the display, affecting product temperature.

