



Product Code: EP1/3L

Freezer three door counter



The versatile Foster EcoPro G3 counter range offers a huge selection of models, build options and accessories to ensure you find the perfect storage solution for your business.

Features & Benefits



- A reduced footprint– the more compact design of G3 counters allow them to fit in the tightest of kitchen spaces without losing capacity
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer - all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- New and improved 'Airlines' ventilation system cools the compressor which reduces running time, saving you energy
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- High performance cyclopentane foam maintains thermal efficiency for longer
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Supplied with helicoil mains lead, allowing easy movement for cleaning purposes
- Operates efficiently in ambient temperatures of up to 43°C

Shelving		Base Fittings		Doors	
Additional S/S Trayslides	Option	Castors 80mm	Standard	Solid	Standard
Additional GN1/1 Shelf	Option	100mm legs in lieu of castors	Option	Product Extras	
Refrigeration		Legs 150mm	Option	Helicoil Mains Lead	Option
R290 - Energy Efficient	Standard	Electrical & Service Data		Splashback	Option
Integral Refrigeration System	Standard	230/50/1	Standard	304 S/S Back and Unit Cover	Option
Remote Refrigeration System	Option	Finish		Energy	
Less Condensing Unit	Option	304 s/s ext & alu int	Standard	kWh (24 hours)	9.84
RH Mounted Ref Unit	Option	304 s/s ext & int	Option	AEC	3592
Specification		304 S/S back for island sitting	Option	Nett Volume	258.4
Gross volume (ltrs)	435			Energy Grade	F
Freezer -18/-21°C	Standard			Global Warming Potential	3
Width (mm)	1815			Energy Efficiency Index	92.36
Depth (mm)	700				
Height (mm)	865				
Worktop	Standard				

Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Adequate airflow must be kept around the counter: 150mm
- Depth with door open is 1113mm
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.

Energy Performance Data and information



Application

This appliance is intended for use in ambient temperatures up to 40°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



The Refrigeration Experts

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.