

# SPD516UK

Product Family	Dishwasher
Subfamily	Traywasher
Basket dimensions	500x500 mm
Panel	Easyline 2016
Filter	5-stages filter system
Rinse pump with H.T.R. system	Rinse pump with atmospheric boiler
Usable load height	400 mm
Default power supply	230 V~ / 30 A / 6,8 kW / 50 Hz
Depth with door open	1020 mm
Dimensions	600x690x822 mm
EAN code	8017709345396



## Target

Potential users	Bakery/Pastry making; Industrial pastry&bakery laboratories; Butcher's shops; Meat processing industry; QSR
-----------------	---

## Aesthetics

Series	Topline	Led colour	Green
Control Panel	Electronic		

## Functions



Functions	Euronorm trays washing; GN 1/1 trays washing; 5- stage filter; HTR; Door clearance 400mm
-----------	---

## Programmes

Programs	6 automatic programs; 1 fully programmable program; Self-cleaning programs
Program options	Extra rinse; Clean water cycle

## Program specifications

Boiler 71°C/Tank 60°C-60"; Boiler 85°C/Tank 60°C-60";  
Boiler 71°C/Tank 60°C-1'20"; Boiler 85°C/Tank 60°C-  
1'10"; Boiler 85°C/Tank 60°C-1'30"; Boiler 85°C/Tank  
60°C-2'30"; Boiler 85°C/Tank 60°C-4'10"

Drain and self cleaning cycle

Yes

Maximum baskets/hour

60

Maximum plates/hour

720

## Interface

Display 8 digit

On/off indicator Yes

Low rinse aid alert Yes

Low detergent alert Yes

Cycle progress indicator Yes

End of cycle indicator Yes

Manual diagnostics Yes

## Construction

Tank Deep drawn

Construction Double wall

Tank material Stainless steel AISI 304

Back panel Galvanized

Door Double skinned

Counter balanced door Yes

Tank filter Stainless steel

Wash arm Stainless steel AISI 304

Rinse arm Stainless steel AISI 304

Door gasket On 3 sides

Rack guides Embossed

Wash tank capacity 11 l

Boiler capacity 6.5 l

Protection class IPX4

Adjustable feet Yes

Net weight (kg) 72.000 kg

Drain max. height 600 mm

## Technical Features

Tank heating element 2000 W

Boiler heating element 6000 W

Wash pump 700 W

Default connection 6700 W

Water consumption per cycle 3,2 l

Warm water connection 8°C

Inlet water maximum temperature 60°C

Max water hardness 12°F - 7°dH

Water inlet pressure 1-6 bar / 100-600 kPa

## Electrical Connection

Plug (G) UK e Singapore

Electrical connection options 230 V~ / 12 A / 2,7 kW / 50 Hz (NC); 230 V~ / 15 A / 3,4 kW / 50 Hz (NC); 230 V~ / 20 A / 4,5 kW / 50 Hz (NC); 400 V 3N~ / 12 A / 6,8 kW / 50 Hz (NC)

## Equipment



Drain pump Yes

Rinse aid flow rate 0.4 l/h

<b>Peristaltic detergent pump</b>	Yes, electronic control	<b>Cycle counter</b>	Yes
<b>Peristaltic rinse aid pump</b>	Yes, electronic control	<b>Break tank</b>	Yes
<b>Chemical level probe</b>	Yes, optional KITSONLIV	<b>Partial water exchange in the wash tank via built-in drain pump</b>	Yes
<b>Chemical dosing</b>	gr/lt	<b>Trays washing option</b>	GN1/1 530x325 mm and EN6040
<b>Boiler thermostat</b>	Yes	<b>Water supply pipe diameter</b>	16 mm
<b>Soft Start</b>	Yes	<b>Drain supply pipe diameter</b>	21.5 mm
<b>Stand-by system</b>	Yes	<b>Detergent (red) hose length</b>	Yes, manual
<b>Automatic start</b>	Yes	<b>Rinse aid (blue) hose length</b>	Yes, manual
<b>Detergent flow rate</b>	1.5 l/h		

## Accessories Included

<b>Plate basket</b>	PB50D01	<b>Tray basket</b>	WB50T03
<b>Cutlery basket</b>	PHOOS02	<b>Water supply pipe</b>	Yes - 2m
<b>Flat basket</b>	PB50G02	<b>Drain pipe</b>	Yes - 2m
<b>Grids</b>	1 x WG500		



<b>R</b>	PANNELLO RETRO LOWER BACK PANEL
<b>Q</b>	MORSETTO EQUIPOTENZIALE EARTH TERMINAL
<b>P</b>	TUBI POMPE PERISTALTICHE PERISTALTIC HOSES
<b>E</b>	CAVO ALIMENTAZIONE ELETTRICA ELECTRICITY SUPPLY CABLE
<b>S</b>	TUBO DI SCARICO DRAIN HOSE
<b>T</b>	ENTRATA CAVO DI ALIMENTAZIONE DOSATORE ESTERNO EXTERNAL DISPENSER POWER CABLE ENTRY POINT
<b>C</b>	TUBO DI CARICO FILLER HOSE

## Not included accessories



### PHOOS01

Single basket in polypropylene for cutlery




### PHOOS02

Basket in polypropylene for cutlery with 6 compartments



### WH00S01

Wire insert for 12 small dishes



### PB50D01

Basket made of polypropylene for 18 plates 500x500




### KITSONLIV

Probe level kit



### WS5

Underframe for glasswashers 500mm



### PB50G02

Universal basket in polypropylene 500x500



### WB50T03

Wire basket for 5 trays 600x500



### WB50T02

Wire basket for 5 trays 600x500



### KITDETKCC500

Kit for detergent (1l) and rinse storage (1l) for dishwashers 500x500



### WB50PG5

Wire basket for no. 25 plastic glasses with flat bottom, 500x500x260 mm



### PHOGR5

Glass basket for 500x500 mm glasswashers

## Symbols glossary

---



SUITABLE FOR EURONORM TRAY



Suitable for 1/1GN trays



HTR rinsing system



Max usable height 400mm



5 STAGE FILTER