

Refrigerated Multi-Tiers

Multi-tier open fronted display

- Open fronted display cabinets, achieves a balanced air temperature throughout the cabinet of between 2°C & 5°C in ambient temperatures up to 27°C at a relative humidity of 50%.
- Microprocessor based temperature control with automatic defrost and condensate handling system.
- Three height adjustable and removable shelves for flexibility of display.
- Illuminated display via integral fluorescent lighting.
- Supplied on castors with height adjustable levelling feet for stability.
- Double glazed rear hinged doors or solid back.
- 304 grade stainless steel top and well.
- Ambient under 1600mm & 1900mm rear hinged door models.



Rear view showing hinged doors

Three tier models 1600mm high	1206mm	1606mm	1906mm
Rear hinged door	CARIB73.712	CARIB73.716	CARIB73.719
Solid back	CARIB73.712W	CARIB73.716W	CARIB73.719W
Two tier models 1430mm high			
Rear hinged door	CARIB72.712	CARIB72.716	CARIB72.719
Solid back	CARIB72.712W	CARIB72.716W	CARIB72.719W

Optional Extra

- Tray Slides
- Removable Plinth

Designed to meet the EN ISO 23953 standard, providing M1 cabinet class conditions and exceeding climate class 3 environment of 25°C at 60% RH.

High Capacity Multi-tier

Open fronted refrigerated display case for positioning adjacent to a wall. Designed to achieve a balanced air temperature throughout the cabinet of between 3°C & 5°C in ambient temperatures up to 27°C.

Product Features

- Microprocessor based temperature control with auto defrost and condensate handling.
- Bright polished stainless steel interior.
- Four height adjustable 6mm thick toughened glass shelves. Ten shelf positions.
- Interior illumination.
- Supplied on castors with adjustable levelling feet.
- Removable stainless steel door plates.
- 13 amp supply.

Optional Extra

- Tray Slides.
- Night Blind.
- Roller Shutter.



CARIB7.1310

1130 x 680 x 1850mm

CARIB7.1315

1550 x 680 x 1850mm

When roller shutter is added unit height increases to 2050mm high.