Model:	Underbar Refrigeration:
SDD-27-90	*27" Direct Draw Beer Dispenser*

SABA



SDD-27-90

- CABINET CONSTRUCTION
  Standard, cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish. Stainless exterior options available. Standard interior construction utilizes stainless steel walls, floor and ceiling.
- REFRIGERATION
  Refrigeration system uses R134a refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.
- ELECTRICAL
  Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet.
- TEMPERATURE
  Oversized, factory balanced, refrigeration system holds 33℉ to 38℉(0.5℃ to 3.3℃)
- SANITATION
  NSF-7 approved for packaged and bottled product.

MODEL FEATURES:

- **Standard LED light inside of the cabinet**
- Easily accessible condenser coil for cleaning, and easy service access
- Designed to accommodate a variety of beer kegs

General Specification

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches / mm)			Capacity	HP	Voltage	Amps	NEMA Config.
			L	D	H	1/2 Barrels				
SDD-27-90	3	6	90 3/8 2295	27 3/4 705	35 5/8 905	4	1/3+	115/60/1	7.5	5-15P

- Height does not include 15 1/4" (388mm) for draft arm.
- Plug type varies by country.
- Height does not includes 3" casters.
- Two-faucets column is option

c ETL US LISTED Intertek

NSF

SABA
Add: 3390 Enterprise Avenue, Hayward, CA 94545-3228
Tel: (510) 293-0189 Fax: (510) 293-0199 E-mail: info@sabacorpusa.com Website: www.sabacorpusa.com

SDD-27-90 Plan View

