
APPLICATION:		PRODUCT NAME:		
		ADD-ON FAUCET WITH SWING SPOUT		
JOB NAME:		SPECIAL CONFIGURATION  CHECK BASE MODEL AND OPTIONS		
QUANTITY:	ITEM NO.	MODEL:		
	I	☐ 2901 WITH 6" SWING SPOUT		
		☐ 2901-8 WITH 8" SWING SPOUT		
		☐ 2901-10 WITH 10" SWING SPOUT		
		☐ 2901-12 WITH 12" SWING SPOUT		
		☐ 2901-14 WITH 14" SWING SPOUT		
		☐ 2901-16 WITH 16" SWING SPOUT		
2-3/4" [70mm]		OPTIONS OR MODIFICATIONS:		
		☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE		
		☐ VANDAL RESISTANT KIT		



MODEL	DIM "A"	DIM "B"	DIM "C"
2901	6"	7-1/8"	10-3/4"
	[152mm]	[181mm]	[273mm]
2901-8	8"	8"	11-5/8"
	[204mm]	[204mm]	[296mm]
2901-10	10"	7-1/2"	11"
	[254mm]	[191mm]	[280mm]
2901-12	12"	8-3/4	12-3/8"
	[305mm]	[222mm]	[314mm]
2901-14	14"	9-3/8"	13"
	[356mm]	[239mm]	[330mm]
2901-16	16"	10"	13-5/8"
	[406mm]	[255mm]	[347mm]

## **FEATURES**

☐ OTHER

## CONTROL VALVE

- \* 3/8" MALE INLET
- \* STEM RIGHT HAND
- \* HOT AND COLD INDEX BUTTONS
- \* SWIVELLING SEAT DISK
- \* STAINLESS STEEL SEAT
- \* STAINLESS STEEL SEAT SCREW
- \* STAINLESS STEEL HANDLE SCREW

## SYSTEM LIMITS

- \* TEMP: 40°F MIN. TO 140°F MAX.
- \* PRESSURE: 200 PSI MAX. STATIC
- \* 2.20 GPM AT 80 PSI

## **SHIPPING WEIGHT**

\* 2.5 LBS

FISHER MANUFACTURING COMPANY