Model:

Traditional Reach-In's:

S-47RG

Reach-In Swing Glass Door Refrigerator:



Rough-In Data

Intertek



S-47RG

- Stainless steel exterior retains attractive finish longer.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Standard door features: Positive seal self-closing door. Duralumin door frame Tempering glass to protect personal safety.
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- **Electronic control system:** Adjustable temperature set point and defrost frequency Error codes to diagnose service issues
- Shelf: Adjustable, heavy duty PVC coated shelves.
- Standard heavy-duty casters make it easy to move and clean underneath

Bottom mounted units feature

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

			Cabinet Dimensions (inches) (mm)			CAP.			Cord Length		
Model	Doors	Shelves	L	D	Н	CU.FT. LITER	HP	Voltage	(total ft.) (total m)	NEMA Config.	
S-47RG	2	6	54 1371	32-1/4 818	82-1/2 2095	47 1321	1/2+	115/60/1 230-240/50/1	9 2.74	5-15P	
			Plug type varies by country.								
c	NSF.	The deepth does not includes the 2-3/8" door handle									



Add: 3390 Enterprise Avenue, Hayward, CA 94545-3228

Tel: (510) 293-0189 Fax: (510) 293-0199 E-mail: info@sabacorpusa.com Website: www.sabacorpusa.com



S-47RG Plan View

