



SERVING THE FOOD INDUSTRY SINCE 1951

Grab-and-Go Black Open Front Refrigerated Showcases

ITEM:	48377	48378	48379	48380
MODEL:	RS-CN-0900	RS-CN-1200	RS-CN-1500	RS-CN-1800



48377



48378



48379



48380

Enhance your retail environment with these sophisticated refrigerated merchandisers to boost product visibility and attract more customers.

The Omcan Grab-and-Go Open Front Refrigerated Showcases are designed to display your products elegantly. They use eco-friendly R290 refrigerant for sustainable cooling and maintains a temperature range of to keep your items fresh. The digital temperature controller provides precise adjustments, and the night curtain helps save energy. For ease of movement, they feature four castors, two with brakes, ensuring stability. The ventilated cooling system and automatic defrost function offer consistent performance, and the four shelves provide



FEATURES:

- Brilliant internal LED illumination on top
- Digital temperature controller and display
- Comes with night curtain
- 4 castors (2 with brakes)
- Ventilated cooling system
- Automatic defrost

Telephone: 1-800-465-0234

Fax: (905) 607-0234

Email: sales@omcan.com

Website: www.omcan.com



Authorized Dealer



48379

48380

48377, 48378

Made in China

(Updated 2026.05 tp)

Page 1 / 3

TECHNICAL SPECIFICATIONS

Features	36" wide with 19.77 cu.ft. (560 L) capacity	48" wide with 26.83 cu.ft. (760 L) capacity	60" wide with 33.9 cu.ft. (960 L) capacity	72" wide with 40.96 cu.ft. (1160 L) capacity
Item	48377	48378	48379	48380
Model	RS-CN-0900	RS-CN-1200	RS-CN-1500	RS-CN-1800
Capacity	19.77 cu.ft. (560 L)	26.83 cu.ft. (760 L)	33.9 cu.ft. (960 L)	40.96 cu.ft. (1160 L)
Number of Doors	1 Pull Down Curtain			
Number of Shelves	4			
Shelf Dimensions	30.1" x 12.3" (764 x 312 mm)	41.9" x 12.3" (1064 x 312 mm)	53.7" x 12.3" (1364 x 312 mm)	65.5" x 12.3" (1664 x 312 mm)
Shelf Material	Glass			
Exterior Material	Glass/Painted Metal			
Interior Material	Plastic/Painted Metal/Stainless Steel			
Number of Casters	4			
Power	1320 W	1600 W	2050 W	2050 W
Lamp Power	50 W	75 W	105 W	115 W
Amps	14 A	15.5 A	19.6 A	11 A
Electrical	110V / 60Hz / 1Ph	110V / 60Hz / 1Ph	110V / 60Hz / 1Ph	220V / 60Hz / 1Ph
Temperature Range	2 - 10°C (35.6 - 50°F)			
Refrigerant	R290			
Injection	490g		285g x 2	250g x 2
Insulation Material	C5H10			
Type of Climate	3			
Interior Dimensions (WDH)	32.9" x 21.1" x 51.2" (835 x 535 x 1300 mm)	44.7" x 21.1" x 51.2" (1135 x 535 x 1300 mm)	56.5" x 21.1" x 51.2" (1435 x 535 x 1300 mm)	68.3" x 21.1" x 51.2" (1735 x 535 x 1300 mm)
Net Weight	364.8 lb (165.5 kg)	431 lb (195.5 kg)	547.8 lb (248.5 kg)	617.3 lb (280 kg)
Net Dimensions (WDH)	36.6" x 28.4" x 80" (930 x 722 x 2030 mm)	48.4" x 28.4" x 80" (1230 x 722 x 2030 mm)	60.2" x 28.4" x 80" (1530 x 722 x 2030 mm)	72" x 28.4" x 80" (1830 x 722 x 2030 mm)

* Dimensions rounded up to the nearest inch or millimeter.
Specifications subject to change without notice.

TECHNICAL DRAWINGS

