

Project
Item #
Quantity

## **CHAR-ROCK BROILERS**

AECB-24 AECB-34

AECB-44 AECB-54

AECB-64

#### STANDARD FEATURES

- True char-broiled flavor with natural volcanic lava rock. Juices drip onto the rocks resulting in searing flames and smoke that enhance flavor
- Individually controlled cast-iron 35,000 BTU/hr. "H" burners, providing maximum output, even heat distribution, flexibility, and low maintenance
- · Manual gas control valve for each burner
- Standing pilots for instant ignition for each burner
- Sectioned top grates individually removable for easy cleaning and can be positioned flat or sloped
- Heavy duty cast iron top grates are angled to control flare-ups
- Stainless steel polished front and trim for easy cleaning with fully insulated double layered steel chassis
- Full-length grease channels drains the run off into a removable pan for easy cleaning
- Two year limited warranty, parts, and labor

GAS TYPE:









#### Model Shown AECB-24

#### DESCRIPTION

American Range AECB series char-rock broilers feature a countertop design and 35,000 BTU/hr. Cast-iron "H" shaped burners. Models come in a range of sizes from 24" to 72" wide. Cast-iron angled top grates. Stainless steel exterior construction makes this charbroiler both durable and easy to clean. Two year limited warranty, parts, and labor.












# CHAR-ROCK BROILERS







Shipping Weight

Model	Burners	Width (mm)	Depth (mm)	Height (mm)	BTU/hr.	(kW)	Crated Dimension (mm)	Lbs	(kg)
AECB-24	2	24" (610)	24" (610)	13 1/4" (337)	70,000	(20)	29" (737) × 30" (762) × 20" (508)	169	(170)
AECB-34	3	36" (914)	24" (610)	13 1/4" (337)	105,000	(30)	41" (1041) × 30" (762) × 20" (508)	327	(241)
AECB-44	4	48" (1220)	24" (610)	13 1/4" (337)	140,000	(41)	53" (1346) × 30" (762) × 20" (508)	465	(352)
AECB-54	5	60" (1524)	24" (610)	13 1/4" (337)	175,000	(51)	65" (1651) × 30" (762) × 20" (508)	600	(272)
AECB-64	6	72" (1829)	24" (610)	13 1/4" (337)	210,000	(62)	77" (1956) × 30" (762) × 20" (508)	740	(336)

- Specify type of gas and altitude if over 2000 feet.
- Please specify gas type when ordering.

### COMBUSTIBLE WALL CLEARANCES:

For use only on non-combustible floors. Legs or casters are required, or 2" (51) overhang is required when curb mounted. Clearance from non-combustible walls is 0". When unit is placed next to combustible walls, clearances must exceed 12" (305) from sides, and 4" (102) from rear. Radiant broilers for non-combustible locations only.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard.

NFPA96 "Vapor Removal from Cooking Equipment." (NOTE: For North America only)

Subject to change without notice.

\*Shipping weight includes packaging and is approximate.

MANIFOLD PRESSURE NATURAL GAS   PROPANE GAS   MANIFOLD SIZE							
5.0" W.C.	10.0" W.C.	3/4" (19MM)					





