

Flexiline



Bains marie hot cupboard - BS30HB

BS30HB

Compact bains marie hot cupboard specifically developed for the primary school meal service, where throughput is high and serving period short. Up to three electrically heated units can be linked together to operate from a single 13 amp socket. Specify height: 800, 825, 850 or 875mm and electrical handing left or right at time of order. Picture shows BS30HB unit in Solent Blue P.C.S with optional TSS30D tray slide and gastronorm containers.

Specifications

Dimensions: External: 1200 x 616 x either 80,0 825, 850, or 875mm Internal: 980 x 545 x height - 525mm

Electrical Connection 220V/240V 1 phase 50Hz 1kW loading 4.1Amps approx Cable: 2 metres with 13 amp plug fitted RCD 13 amp socket for connecting adjoining unit.

Exterior: Stainless Steel or plastic coated steel, Interior: Galvanised Steel.

capacity: No well, direct heat from hot cupboard 3 x GN1/1 x 150mm deep Hot cupboard capacity: 6 x GN1/1 x 150mm containers (875mm high unit)

Construction

Top: Stainless Steel,
Capacity Bains Marie

Features

Standard Features:

- Extended stainless steel tops to both ends enables a continuous servery to be formed.
- On/off thermostat control to hot cupboard
- Double skin fully insulated construction reducing heat loss for safe & efficient operation.
- Fully GN1/1 gastronorm compatible.
- Heat to bains marie is from hot cupboard
- Three removable shelves & supports.
- Removable element cover to maximise access for cleaning.
- Robust push/pull bar to both ends
- Removable sliding doors.
- Four x 100mm swivel castors two braked.

Options

- [Quartz heated gantry](#)
- [Trayslide](#)
- [Choice of colour finish](#)
- Gastronorm containers
- Left or right handed cable exit and interconnecting

Victor Manufacturing Limited

Lonsdale Works, Gibson Street, Bradford, BD3 9TF, West Yorkshire, England
Tel: +44 (0)1274 722125 Email: email@victormanufacturing.co.uk
Copyright © 2014 Victor Manufacturing Limited