

FRY TOP S GAS M40 AISI plate - smooth - Top version

Project:
Rev.:
Zone:
Location:



CODICE
CR1651769

MODELLO
D92/10TSFTGA

SERIE
DIAMANTE90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently.
External coatings and feet in stainless steel with Scotch Brite finish.
Working table height adjustable from 840 to 900 mm.
Range modularity: 200-400-600-800-1200
Wide range of accessories.

TECHNICAL SPECIFICATIONS

15 mm thick cooking plate totally independent of the hob .
Large floodable channel around the perimeter of the hotplate for collecting cooking residues, sloping towards the front for draining liquids into the large drawer.
Large grease collection drawer.
Uniform baking temperature over the entire plate.
Optimising heat in the cooking area and increasing the comfort of operators in the kitchen.
Plate not welded to the machine bed with optimisation of structural points under thermal stress
Stainless steel overflow plug, supplied as an accessory, for channel flooding management
Non-welded plate for fast maintenance and replacement in the utility
New version with identical cooking surface area and reduced energy output.
An increase in output per cm² allows a reduction in consumption of up to 15% compared to conventional versions
Tubular burner with self-stabilising flame with great uniformity of heat distribution.

Floodable gutter for collecting cooking residues around the perimeter of the cooking plate easier cleaning and better retention of moisture in cooking food

Capacious grease collection drawer with capacity for the entire volume of the perimeter channel

Grooved plate design ensures cleanliness right to the end of the plate

Non-welded plate for fast maintenance and replacement in the utility

Plate not welded to the machine bed with optimisation of structural points under thermal stress

Thermal cutting that facilitates the user and adjacent machinery.

Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen.

Water dispenser kit available as an accessory

FRY TOP S GAS M40 AISI plate - smooth - Top version

Project:
Rev.:
Zone:
Location:



CODICE CR1651769	MODELLO D92/10TSFTGA	SERIE DIAMANTE90
---------------------	-------------------------	---------------------

Technical Information

SPECIFICATION	DATA
MATERIAL	CR1651769
DEFINITION	D92/10TSFTGA FTG SMOOTH 430 M40 TOP
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	400 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	250 mm
NET WEIGHT	47,000 Kg
VOLUME (net)	0,090
PACKAGE LENGTH	440,000 mm
PACKAGE WIDTH	1020 mm
PACKAGING HEIGHT	550,000 mm
PACKAGE VOLUME	0,248 m3
GROSS PACKING WEIGHT	55,000 Kg
GAS POWER	7,00
GAS POWER (G25.3/25mbar)	7,00
CERTIFIED MODEL	D92/10TSFTG

FRY TOP S GAS M40 AISI plate - smooth - Top version

Project:
Rev:
Zone:
Location:




CODICE
CR1651769

MODELLO
D92/10TSFTGA

SERIE
DIAMANTE90

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm
MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda

E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwarte - Entrada cabo eléctrico	G Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligação gás EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)
S Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água	H20 Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de agua - Wateraansluiting - Junção alimentação água
S1 Scarico vasca - Wannenabflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba	A1 Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno A2 Fredda - Kalt - Cold - Froid - Fria - Koude - Frio
S2 Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de depresión - Onderdrukklep - Válvula de depressão	
S3 Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de agua intersticios - Afvoer water tussenruimte - Descarga de água na marmitta com Sistema de aquecimento indirecto	
S4 Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulação de dreno	L Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nível - Niveaakraan - Torneira de nível

FRY TOP S GAS M40 AISI plate - smooth - Top version

Project:
Rev.:
Zone:
Location:



CODICE
CR1651769

MODELLO
D92/10TSFTGA

SERIE
DIAMANTE90

Product's PLUS






Plate not welded to the machine bed with optimisation of structural points under thermal stress




Capacious grease collection drawer with capacity for the entire volume of the perimeter channel



Thermal cutting that facilitates the user and adjacent machinery.




Grooved plate design ensures cleanliness right to the end of the plate



Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen.



Non-welded plate for fast maintenance and replacement in the utility



Water dispenser kit available as an accessory

FRY TOP S GAS M40 AISI plate - smooth - Top
version

CODICE
CR1651769

MODELLO
D92/10TSFTGA

SERIE
DIAMANTE90

Project:
Rev.:
Zone:
Location:



Water dispenser kit available as an accessory

FRY TOP S GAS M40 AISI plate - smooth - Top version

Project:
Rev.:
Zone:
Location:



CODICE
CR1651769

MODELLO
D92/10TSFTGA

SERIE
DIAMANTE90

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1354989	PRPC	
CR1354999	PKLR	
CR1356399	RPR	Striped chrome plate scraper
CR1658619	97CPFT4	M40 fry top cleaning drawer
CR1658609	97TFT	
CR1658669	9AFT4	
CR1659159	Q94GKSCFT	
CR1658839	Q794CAFT	