

Product data sheet — Gas boiling top with 4 burners

MKN-No.:
1263402

Range according to DIN 18851 for all-purpose application in commercial kitchens. For the preparation of dishes in saucepans and pans on one surface. For boiling, steaming, frying, braising, simmering and steam frying.



Technical highlights

Material:

Casing and cover are made completely of CNS (material No. 1.4301) / AISI 304.
Visible surfaces with polished and satin finish, 320 grit.

Bendings:

Cover bent downwards 30 mm at the front and bent upwards 20 mm at the rear. Designed as a drip edge at the front. 50 mm cover projection closed to the appliance body.

Body:

Buckling resistant, self-supporting, closed construction with side walls, rear wall and bottom.

Control panel:

Operation panel desk-shaped for highest ergonomic requirements and very easy cleaning. Removable from the front for easy and cost efficient service access.
Ergonomiacally shaped knobs for a easy identification of the position.

Effective area:

CNS/stainless steel hob with large radii, easy to clean, seamlessly and tightly deep drawn 70 mm to the cover plate. The burners which are sealed downwards have atmospheric burner heads. Removable sliding grid 350 x 700 mm of CNS/stainless steel (for two burners).

Installation:

Equipped for installation of a 580 mm high Counter SL lower section with removable appliance feet (150 mm high) which are adjustable in height.

Type of energy:

Appliance is completely tubed internally in accordance with gas requirements. Gas connection by means of a gas appliance tube attached to a gas socket (DN 15) with shut-off valve.

Special feature:

Heating:

Heating by atmospheric burner heads, thermoelectrically protected. Ignition burner and thermoelement protected by a removable cap. Nozzle and primary air aperture of the ignition burner protected under the hob.
The heating power setting occurs by means of a thermoelectrically protected multi-gas tap for each cooking zone. Gas cut off cock integrated in the panel.

Product data sheet — Gas boiling top with 4 burners

MKN-No.:
1263402

Range for the preparation of dishes in saucepans and pans on one surface. For boiling, steaming, frying, braising, simmering and steam frying.

Current drawings you will find here:
www.mkn.com
► Partner Login
► spare parts database & download

Further features

- connection, sealing by means of patented connecting method – clamp bar is rounded (R 20) at the back for easier cleaning

Technical data

Dimensions (LxWxH*) (mm):	800 x 700 x 270
Effective area:	4
Dim.: effect. area (LxWxH) (mm):	350 x 275 x 70
Diameter (mm):	
Nominal capacity (L):	
Nominal fill quantity (L):	
Connected load (electrical) (kW):	
Voltage ¹ (V):	
Recommended fuses (A):	
Frequency range (Hz):	50/60
Rated heat load (kW):	18,2
Standard gas pressure – natural gas ² (mbar):	20; 25
Standard gas pressure – liquid gas ² (mbar):	30; 37; 50
Gas connection:	DN 15 (1/2")
Heat-up time (Min.):	
Vapour pressure (bar):	
Refrigeration capacity (kW):	
Net weight (kg):	50
Gross weight ³ (kg):	60
Heat emission latent (W):	1820
Heat emission sensitive (W):	4550
Type of protection:	

* Carcass height plus optional appliance feet with a height of 150 mm or 200 mm

Product safety

- CE mark

Installation requirements

- gas connection provided by customer

Option / accessories

MKN-No.:	Description:
10016884	CNS-grid (274 x 370 mm)
201860	simmering plate for one C-burner
201568	all-gas socket, 1/2", with gas tube, 1/2" x 800 mm

¹ special voltages on request

² further types of gas on request

³ seaworthy packing on request



Subject to change without notice!
28.05.2020