



# 50Hz

# iT0500 Ice Cube Machine

### Models

IRT0500A IDT0500A IYT0500A



## Ice Machine Electric

### **Minimum Circuit Ampacity:**

Air-cooled: 5.6 Maximum Fuse Size: Air Cooled: 15 amps

Specifications

BTU Per Hour:

3,800 (average),

Refrigerant:

by 48%

and 6,000 (peak)

R410A CFS - Free

Lowers global warming

### **Operating Limits:**

Ambient Temperature Range: 40° to 110°F (4.4° to 43.3°C) Water Temperature Range: 40° to 90° F (4.4° to 32.2° C)

> · Water Pressure Ice Maker Water In:

Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo NXT Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

- New levels of Performance Showcasing an average of 12% lower energy consumption and a 23% reduction in condenser water usage. This translates into lower cost of ownership over the life of your machine.
- easyTouch® Display New icon based touch screen takes the guess work out of owning and operating an ice machine.
- Multiple Language Capability The easyTouch display is available in multiple languages selected in the initial start-up installation Wizard
- Programmable Ice Production Now its super easy to program your ice machine to be off at certain times of the day to save money with fluctuating electrical rates. Also programmable by daily ice production volume and night tine programming.
- Easy to Clean Foodzone Hinge front door swing out for easy access. Removable water-trough, distribution tube, curtain, water probe and water pump for fast and efficient cleaning. Selected components are made with AlphaSan® antimicrobial.
- Intelligent Diagnostics Provides 24 hour preventative maintenance and diagnostic feedback for trouble free
- Acoustical Ice Sensing Probe Unique patented technology allows for reliable operation in challenging water conditions
- Available LuminIce® II Virus and Bacteria Inhibitor Controls viruses, bacteria, mold and yeast within the food zone to keep the machine clean longer. A new sanitation icon lets you know the operational status.
- Active Sense insures consistent ice harvest in all environmental conditions. This software solution works in conjunction with the acoustical ice sensing probe improving reliability and performance.



# Ice Shape







#### 7/8" x 7/8" x 7/8" (2.22 x 2.22 x 2.22 cm) Cube weight 8.5 g















# 50Hz



# iT0500 on D-570 Storage Bin




- (water-cooled units)
- 1/2" (1.27 cm) Auxillary Base Drain Socket
- (E) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet (F) 1/2" (1.27 cm) F.P.T. Ice Making Water Drain
- (G) 3/4" (1.91 cm) Bin Drain

#### Installation Note Minimum installation

clearance:

Top/side: 12" (30.50 cm)Back is 5" (12.7 cm)



1.75" (4.45 cm) 4.00" (10.16 cm)

5.25" (13.34 cr 6.75" (17.15

13.00" (33.02 cm

### Space-Saving Design





	iT0500 D-400	iT0500 D-570	
Height	59.50" 151.13 cm	71.50" 181.61 cm	
Width	30.00" 76.2 cm	30.00" 76.2 cm	
Depth	34.00" 86.30 cm	34.00" 86.30 cm	
Bin Storage	365 lbs. 165.7 kgs.	532 lbs. 241.1 kgs.	

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm). Bin capacity is based on 90% of the volume x 33 lbs/ft3 average density of ice.

# Specifications

			lce Production 24 Hours		Power Usage kWh 45.4 kg / 100 lbs @ 32°Air / 21°C Water 90°Air / 70°F Water	Potable Water
	Model	lce Shape	21°Air /10°C Water 70°Air/ 50°F Water	32°Air / 21°C Water 90°Air/ 70°F Water	1 Ph	Usage/100 lbs. 45.4 kgs. of Ice
AIR COOLED	IRT0500A	Regular	480 lbs.	370 lbs.	5.04	19 Gal.
	IKTUSUUA		218 kgs	168 kgs	5.04	71.9 L
	IDT0500A dice	500 lbs.	385 lbs.	5.25	19 Gal.	
			227 kgs	175 kgs	5.25	71.9 L
	IYT0500A	half-dice	515 lbs.	420 lbs.	4.87	19 Gal.
			234 kgs	191 kgs		71.9 L

21.50" (54.61 cm)

44.00" (111.76 cm)

This product is hermetically sealed and contains luorinated greenhouse gas R410A Order ice machine and bin separately

#### Accessories

#### LuminIce® II Virus and **Bacteria Inhibitor** controls viruses and bacteria inside the ice machine.



#### External Scoop holder

protect the ice scoop with the NSF approved versatile scoop holder.



#### **Arctic Pure® Plus Water Filters**

reduce sediments and chlorine contaminants down to .5 microns. Use with a Pre-filter is recommended.



6647B\_50Hz\_10/202

Welbilt reserves the right to make changes to the design or specifications without prior notice.

Welbilt Deutschland GmbH Auf der Weih 11 D - 35745 Herborn, Germany Tel.: +49 27 72 58 050 welbilt.com.de

Welbilt Iberia, S.A.U Textil, 6 - Pol.Ind. La Ferreria - 08110 Montcada i Reixac Barcelona, Spain Tel.: +34 902 20 10 69 welbilt.com.es

Ashbourne HouseThe Guildway Old Portsmouth RdGuildford GU3 1LRUnited KingdomTel.: +44 1483 464900 www.welbilt.uk

