



Product Code: HR150G

Refrigerated Undercounter Cabinet with Glass Door (no light)



Features & Benefits

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate in ambient up to 25°C
- Supplied with glass door.

External Finish

s/s ext Standard

Base Fittings

Castors - Rear Fixed Standard

Levelling Bolts Standard

Electrical, Service & Ecodesign Data

230/50/1 Standard

Fuse Required 13

Internal Finish

aluminium Standard

Doors

Glass Standard

Specification

Dimensions (Width) 605

Dimensions (Height) 830

Dimensions (Depth) 640

Gross Volume 150

Noise DbA @ 1M 68.8

Shelving

Nylon Coated Shelf Option

Refrigeration

R134a - Industry Standard Standard

R290 - Energy Efficient Option

Integral Refrigeration System Standard

Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for airflow, ensure that 25mm clearance is allowed above the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet



Application

This appliance is intended for use in ambient temperatures up to 40°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care