

REFRIGERATOR COMPACT K220R DR G U

Product series: Compact

Item number: 151220030

The HOSHIZAKI COMPACT K220R DR G U is a REFRIGERATOR on castors with a net usable volume of 77 Ltr.

The COMPACT series offers a rare combination: These cabinets are food-safe, space-saving, and come with excellent energy ratings for their class. With a footprint of only 59.5 x 66.7 cm, these small space storage cabinets are easy to fit in, especially when space is limited. These specifications make the series such a popular choice for those operators who do not require heavy-duty Gastronorm equipment.

Food Safety

Thanks to the Hoshizaki air distribution system, temperatures are correct and uniform throughout the entire cold room, ensuring perfectly food-safe temperatures at all times

Low-Running Energy Costs

The Energy Efficiency Class of the COMPACT K220R DR G U is A++. The COMPACT series offers a range of extremely energy-efficient refrigeration units for small spaces.

Comfortable Work Environment

Contributes to a healthier work environment with low noise levels 38.8 dB(A), when the compressor is running. Low heat emission due to short compressor running times.

Hygiene & Ergonomic Design

The COMPACT series features several design extras, implemented to simplify daily cleaning routines. One of the features for optimized operator safety is the full-height integrated handles.

The COMPACT K220R DR G U comes with:

Refrigerant: The REFRIGERATOR uses HC refrigerant R600a

Air circulation system

Right-hand hinged door

Integrated full-height door handle

Internal LED light

Reversible door

Door lock for extra security

White shelves

Automatic defrost with re-evaporation of defrost water



SPECIFICATIONS

Product title	REFRIGERATOR	Energy consumption (kWh/Year)	197
Temperature Range	+1/+12°C	Energy efficiency class standard	ISO 22041-2019
Volume, Gross (ltr.)	123	Energy efficiency class	A++
Net Usable Volume (ltr.)	77	Energy Efficiency Index EEI	9.92
Exterior	Stainless	Sound Level – dB(A)	38.8
Interior	White Finish	Climate Class	4 (max. ambient temp. of 30 °C with 55% RH)
Dimensions W x D x H (mm)	595 x 645 x 833	Refrigerant (kg)	0.036
Weight, Packed (kg)	52	CO2 equivalent (kg)	0.108
Insulation (mm)	52 (polyurethane)	GN or Tray Size (mm)	Shelf 483.8 x 433 mm
Refrigerant	R600a	Maximum number of shelves	9
GWP	3	Number of shelves	2
Ref. capacity at -10°C (Watt)	63	Equipped with	Right hand hinged reversible door with lock, 2 white shelves, bottom shelf 484.7 (W) x 300 (D) mm. Exterior: Stainless. Interior: PS lining in white
Power Supply	230V, 50 Hz	Door Type	Insulated Door
Connection Load (Watt)	70		