Model:

24" Back Bar Cooler:

SBB-24-48G

Glass Swing Door Back Bar Cooler with LED Lighting





SBB-24-48G

- CABINET CONSTRUCTION
 Standard, cabinet exterior
 construction includes attractive, wear
 resistant vinyl on steel in black finish.
 Stainless exterior options available.
 Standard interior construction utilizes
 stainless steel walls, floor and ceiling.
- REFRIGERATION
 Refrigeration system uses R134a
 refrigerant, which is CFC and
 HCFC-free for compliance with environmental safety concerns.
- ELECTRICAL
 Units wired at factory and ready for connection to a 115/60/1 phase,
 15 amp dedicated outlet.
- TEMPERATURE
 Oversized, factory balanced,
 refrigeration system holds 33°F to
 38°F (0.5°C to 3.3°C)
- SANITATION
 NSF-7 approved for packaged and bottled product.

MODEL FEATURES:

- Standard LED light inside of the cabinet
- Easily accessible condenser coil for cleaning, and easy service access
- Tempered glass to avoid injury by broken glasses

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

| Chart annother to an add up to the free for the first to a desired to the first to | | | | | | | | | |
|---|-------|----------------------------------|---------------|---------------|---------------------|----|------------------------|------|--------------|
| | | Cabinet Dimensions (inches / mm) | | | | | | | |
| Model | Doors | L | D | н | Capacity | HP | Voltage | Amps | NEMA Config. |
| SBB-24-48G | 2 | 48 7/8 1240 | 24 3/8 620 | 35 5/8 905 | 11.8 cu.ft. 335L | | 115V/60Hz 220V/50Hz | | 5-15P (i) |



- Plug type varies by country.
- Height does not includes 3" casters.

5/3/

SBB-24-48G Plan View



