

Specification/Datasheet

Stand II model XS 6-2/3 - Fixing (MarineLine)



Article number

60.31.057

Description

The stand I ensures safe installation of the iCombi Pro XS, CombiMaster Plus XS and SelfCookingCenter XS. The cooking system can be fixed on the base frame using a mounting kit.

Intended use

This product is intended exclusively for professional use, such as in restaurant kitchens or catering operations for schools, hospitals, or delis. Any other use runs counter to its intended purpose, and could be dangerous. RATIONAL AG assumes no liability for consequences of improper use.

Features

- Special feet for direct floor mounting
- Containers secured to prevent slipping
- Height-adjustable feet
- Mounting kit for fixing the cooking system on the base frame
- 8 sets of support rails with 2 storage compartments and intermediate level
- Two-sided opening with side panels and top panel

Capacity

2/3 GN	Grid	8 x
2/3 GN	3/4 in (20 mm) deep	8 x
2/3 GN	1 1/2 in (40 mm) deep	8 x
2/3 GN	2 1/2 in (65 mm) deep	8 x
2/3 GN	4 in (100 mm) deep	4 x

Use of other containers: 1/3 GN, 1/2 GN, 2/3 GN

Technical specifications

Clearance from floor panel to floor:	5 7/8 in (150 mm)
Max. fixed power:	1,320 lb (600 kg)
Width of racks:	13 in (329 mm)
Feet height adjusts by up to:	1 1/8 in (28 mm)

Dimensions and weights

Width (W):	27 1/8 in (689 mm)
Height (H):	36 3/4 in (932 mm)
Depth (D):	24 1/8 in (613 mm)
Weight:	92.6 lb (42 kg)

Material

Stainless steel (CNS 1.4301/AISI 304)

Note

USPH regulations require that the stand remain fully accessible from two opposing sides for cleaning purposes. If this is not possible, at least 7 7/8 in (200 mm) of ground clearance must be maintained.

