

# Cabinet Stand 700

## Induction cooker with 2 zones

**Manufacturer: Locher GmbH**

**Model: 207200**



### **Description:**

Powerful free-standing induction cooker module with two zones – open base.

Module made entirely from 304 grade stainless steel with flush mounted ceramic glass plate. Rounded angles and smooth surfaces enable easy cleaning of the unit. Inspection cover, back cover and lower division plate are removable for servicing. 4 adjustable feet that can be removed for installation on a full or hollow pedestal. 20 mm backslash on the rear.

Energy transmission through induction coils underneath the ceramic glass. The generator is positioned under the coil. In the case of maintenance, the connectors of the generator can be easily disconnected.

### **Utmost operational security thanks to:**

- Electronic energy monitoring.
- Empty pan detection (in the centre of the zone reduces power and turns off automatically)
- Electronic temperature control for the protection of the coil, the generator and the PCB
- Hot hob indicator

Each zone is operated through a potentiometer. Unit comes with power on/off main switch with indicator lamp. An LED display under glass shows the selected power level (1-9) and any malfunctions. Each generator has two integrated fans, so air circulation is guaranteed. Unit comes with power cable, air duct and a dishwasher safe metallic air filter.

### **Optional:**

- Preparation for energy optimisation
- Interlock strip
- Castor Set
- Hinged doors for lower compartment (left or right handed)
- Professional scraper for ceramic glass (PCS/PCSB)
- Kit for ceramic glass care and cleaning (CPPS)

### **Technical data**

Width:	400 mm
Depth:	700 mm
Height:	850/900 mm (Height of lower compartment: 700 mm)
Glass dim.:	350 x 605 x 6 mm
Coil dim.:	2 x round Ø 260 mm with 3,5 kW each
El. conn.:	400 V/3ph /7,0 kW

Dimensions and images are indicative. We reserve the right to modify any data without prior notice.  
Shown colours may differ due to printing process.

