



- All aluminum construction
- Furnished with 16 pair of 5-1/2" removable universal pan supports
- Accommodates a wide range of pans and screens from 17" to 23" wide and up to 26" deep, including 18" x 26" trays and steam table pans
- Includes dual purpose HHP-SB-EXT to use for proofing or holding
- Pan stop provides even heat distribution throughout cabinet
- Full height unit - will accommodate up to 16 full size sheet pans at 3" centers - smaller spacing could accommodate additional pan supports (sold separately).
- Integrated side handles on cabinet and magnetic latch handle on doors
- Ambient air temperature may affect heating performance
- Large Plate Series Casters - 6" PU swivel, 2 w/brakes

Bottom mount removable heat unit for easy maintenance and repair includes external cabinet controls



Digital thermometer in face of heat unit Temp adjustable to approximately 165°F in Hold for non-insulated cabinets



Hold provides dry heat only while Proof provides lower temps with humidity



Separate temperature and humidity controls

- 120 volt, 1700 watt, 60 cycle, single phase
- 8-foot cord with NEMA 5-20P plug
- Dedicated 20 amp circuit required



MODEL #	DOOR TYPE	CENTER SPACING	OUTSIDE DIMENSIONS H x W x D (INCHES)	SHEET PAN CAPACITY	WEIGHT (LBS.)
CA72-PF-CD-R	FULL CLEAR DOOR	1-1/2"	74-9/16 x 28-1/2 x 35	Up to 35	189
CA72-PF-CDD-R	CLEAR DUTCH DOOR	1-1/2"	74-9/16 x 28-1/2 x 35	Up to 35	195
CA72-PF-SD-R	FULL SOLID DOOR	1-1/2"	74-9/16 x 28-1/2 x 35	Up to 35	192
CA72-PF-SDD-R	SOLID DUTCH DOOR	1-1/2"	74-9/16 x 28-1/2 x 35	Up to 35	211

Cabinet Options:
• Bumpers
• Hasp lock
• Push Handle
• Drip Pan

(-R) Right hinge is standard, indicate -L for left hinge. *Left hinge are non-returnable.

