Oasis

Refrigerated Self-Service Case 34"D

Structural Concepts®
DELIVERING FRESH. ALWAYS.™

• **B37R**	35-5/8"L x 34-1/4"D x 82-1/4"H
• **B47R**	47-5/8"L x 34-1/4"D x 82-1/4"H
• **B57R**	59-5/8"L x 34-1/4"D x 82-1/4"H
• **B67R**	71-5/8"L x 34-1/4"D x 82-1/4"H

B37R

Included

- Casters (non-locking) w/ levelers
- Condensate pan
- E-Coated evaporator coil
- Hydrocarbon refrigerant (R290)
- Magnetic air filter
- One piece formed ABS plastic tub
- One year parts & labor; 5 year compressor warranty
- Rear wall spacer (removable to fit through door opening)
- Top light (LED 4000K)
- Warmest average product temperature of 40°F or less

Specify	Standard Features	Additional Options
EXTERIOR COLOR	• Powder coated Silversan Black	• Laminate (stock/non-stock colors) • Powder coated (stock/non-stock colors) • Stainless steel
INTERIOR COLOR	• Powder coated Silversan Black	• Powder coated Designer White • Stainless steel
LOWER FRONT PANEL COLOR	• Powder coated Silversan Black	• Stainless steel (must choose stainless exterior)
REAR EXTERIOR COLOR	• Powder coated Silversan Black	• Stainless steel
BASE SUPPORT	• Casters (non-locking) w/ levelers	• Casters (non-locking) w/ seismic levelers • Levelers (remote)
END PANELS	• Full w/stainless steel mirror interior	• Cutaway w/ glass • None (synchronized defrost required)
COVER/CURTAIN	• None	[1] • Night curtain, retractable, non-locking • Removable solid security cover, locking • Roll-down security cover, locking
PRICE TAG MOLDING	• None	• Universal price tag molding (clear w/ open top)
REAR DOORS	• None (solid back panel)	• Rear loading hinged doors, locking
SHELVING	• Metal shelves (4), non-lighted	• Metal shelves (4), lighted (LED 4000K) • Metal shelves (5), lighted (LED 4000K) • Metal shelves (5), non-lighted
ELECTRICAL ACCESS	• Bottom electrical access	• Top electrical access
ELECTRICAL CONNECTION	• 6' Straight blade power cord (self-cont.)	• 6' Locking power cord (self-cont.) • 6' Straight blade 120V power cord, required for B37R 120V (self-cont.) • Electrical leads (remote)
CLEAN SWEEP	• None	• Clean Sweep® automatic condenser coil cleaner
REFRIGERATION	• Breeze~E (Type-II) self-contained refrigeration	• Breeze (Type-I) self-contained refrigeration, required for B37R 120V. Includes separate cord/plug for condensate overflow pan [2] • Remote w/thermostat, solenoid & TXV
THERMOMETER	• Spirit filled thermometer	
MISCELLANEOUS		• Second year parts & labor warranty (excludes compressor)
ACCESSORIES		• End panel lineup seam cover (black/stainless) [3] • Separate cord/plug for condensate overflow pan • Stainless steel milk crate drip pans

Option Notes: 1 - One cover/curtain type per model
2 - Read important notes for remote options
3 - B47R, B57R, B67R only

Oasis

Refrigerated Self-Service Case 34"D

Structural Concepts
DELIVERING FRESH. ALWAYS.™

Intended Environment:	Type II - Designed to operate in ambient conditions of 80°F and 55% relative humidity unless noted otherwise in system information below.	
Zone	**Intended Product To Be Displayed**	**Warmest Avg Prod Temp ° F**
1	Packaged refrigerated products-Prechilled to Warmest Avg Prod Temp.	40

PLAN VIEW



NOTE:
SELF-CONTAINED REFRIGERATION ACCESS ONLY BY PULLING OUT CONDENSER DRAWER.

MODEL	A
B47R	21 3/4"
B57R	27 3/4"
B67R	31 3/4"

SIDE VIEW





NOTE: ALL DIMENSIONS APPROXIMATE

- ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).
- LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH $\frac{3}{4}$" OR 1$\frac{1}{2}$" PVC TUBE).
- REFRIGERATION LINE CONNECTION.
- REMOTE FLOOR SINK & UTILITIES ACCESS AREA.
- SELF-CONTAINED CASE SERVICE ACCESS AREA.
- DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications

Model	L"	L1"	L2"	System Circuit Volts			Phs	Freq	Amps ***	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt
B37R	33.13	35.63	6.25	Remote (DX)	Circuit #1	110-120	1	60	2.22	101	2+G	Leads Single	20.00	4051	3751	850
				Remote (DX)	Circuit #1	110-120	1	60	2.22	101	2+G	Leads Single	20.00	4051	3751	
				Self-Contained (R290)	Circuit #1	208-240	1	60	10.77	1,779	2+G	6-15P or L6-15P	N/A	N/A	N/A	
				Self-Contained (R290)	Circuit #1	208-240	1	60	10.77	1,779	2+G	6-15P or L6-15P	N/A	N/A	N/A	
				Self-Contained (R290)	Circuit #1	110-120	1	60	11.64	1,065	2+G	5-20P or L5-20P	N/A	N/A	N/A	
				Self-Contained (R290)	Circuit #1	110-120	1	60	11.64	1,065	2+G	5-20P or L5-20P	N/A	N/A	N/A	
B47R	45.13	47.63	6.25	Remote (DX)	Circuit #1	110-120	1	60	2.27	120	2+G	Leads Single	20.00	5441	5038	900
				Remote (DX)	Circuit #1	110-120	1	60	2.27	120	2+G	Leads Single	20.00	5441	5038	
				Self-Contained (R290)	Circuit #1	208-240	1	60	16.00	2,807	2+G	6-20P or L6-20P	N/A	N/A	N/A	
B57R	57.13	59.63	6.25	Remote (DX)	Circuit #1	110-120	1	60	2.32	140	2+G	Leads Single	20.00	6299	5833	1,100
				Remote (DX)	Circuit #1	110-120	1	60	2.32	140	2+G	Leads Single	20.00	6299	5833	
				Self-Contained (R290)	Circuit #1	208-240	1	60	16.00	2,826	2+G	6-20P or L6-20P	N/A	N/A	N/A	
B67R	69.13	71.63	6.25	Remote (DX)	Circuit #1	110-120	1	60	2.36	160	2+G	Leads Single	20.00	8222	7613	1,300
				Remote (DX)	Circuit #1	110-120	1	60	2.36	160	2+G	Leads Single	20.00	8222	7613	
				Self-Contained (R290)	Circuit #1	208-240	1	60	16.00	2,846	2+G	6-20P or L6-20P	N/A	N/A	N/A	

*** Does not include electric defrost on freezer models.

Regulatory Approvals:	
All Models	Accordance with AHRI Std 1200 ETL Listed to UL 471 & UL 60335-2-89 ETL Listed to CAN/CSA 22.2 No. 120 ETL Sanitation to NSF/ANSI 7

In Accordance with AHRI Std 1200

DOE 2017 Energy Efficiency Compliant

Important Notes:

1) REMOTE REFRIGERATION NOTE: Condensing unit not included, floor drain required.
2) Performance issues (product temperatures, water on floor, etc.) caused by adverse conditions are not covered by warranty.
3) Levelers must be adjusted during installation to ensure unit is level and plumb.
4) Keep unit at least 15' from exterior doors, overhead HVAC vents, or any air curtain disruption.
5) Do not expose unit to direct sunlight or any heat source (ovens, fryers, etc.).
6) End panels must be tightly joined or kept at least 6" away from any structure to prevent condensation.
7) Tile floors, low ceilings, or small rooms will increase noise level.
8) Compressor air intake at lower front, discharge from lower rear. Lower panels cannot be blocked. Wall spacers required for proper air flow.

⚠ **WARNING:** This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.