



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-3S C CI 230V 1N 50Hz

19097970

24/01/2024

DENOMINATION:

Refrigerated counter - Concept 600 Snack with 3 doors, at 50Hz.

DESCRIPTION :

- High quality austenitic stainless steel inside and outside
 - 50 mm, 40 kg/m³ injected polyurethane insulation.
 - Forced draught cooling system inside the room.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - Easier loading and unloading thanks to its door self-closing and stay open features.
 - Removable and height adjustable plastic covered steel shelves for easy cleaning. Grid self-dimensions: 405 x 460 mm.
 - Equipment: 1 grid per door and 1 set of tray slides.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Interior LED lighting (only for models with glass doors).
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - 10 cm high splashback.
 - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
 - Tested in climate class IV
- Refrigerated counter.

POSSIBLE OPTIONS :

- Stainless Backing
- Legs instead of castors
- Without splashback
- Door frame resistance
- Glass door
- Drawers [1/2] unit
- Locks
- Left group
- Without breastplate
- Without Countertop
- Panoramic aperture
- Drawers [1/3] unit
- Drawers [1/3 + 2/3] unit

POSSIBLE ACCESSORIES :


- REFRIGERATION
- ACCESSORIES
- ACCESSORIES FOR REFRIGERATION

SUPPLIED ACCESSORIES:

- 12034847 Central grid Epoxi (405x525) 1
- 12034975 Side grill in Epoxi(405x460) 2
- 12037728 Support for Snack grid 12

DIMENSIONS

X Width	2017 mm	X Gross width	2160 mm
Y Depth	600 mm	Y Gross depth	680 mm
Z Height	850 mm	Z Gross height	1000 mm
Net Weight	119,0 kg	Gross Weight	125,0 kg
Net volume	1,029 m ³	Gross volume	1,462 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	0,96 A
Electric frequency	50Hz
Electric power	0,203 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Annual elec. consumption	931,00 kWh
Clasif. Energy efficiency	C
Climate class	4
Cooling gas load	64,000 g
Energy Efficiency Index	39,10 %
Gross internal volume	416 L
Model Type	Counter Cabinet
Power consumption 24h	2,55 kWh
Refrigeration net.vol	231 L
Refrigeration power	0,361 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Condensation system	Vent.
Number of doors	3





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-3S C CI 230V 1N 50Hz

19097970

24/01/2024

