

Drop-In Drop-in bain-marie, with one well (3 GN container capacity)

ITEM # _____
 MODEL # _____
 NAME # _____
 SIS # _____
 AIA # _____



341001 (D01H3)

Drop-in bain-marie, with
one well (3 GN container
capacity)

Short Form Specification

Item No.

Designed to be positioned in flush installation providing improved cleanability and suitable for modern design installations. Designed to serve the food in gastronorm containers with a maximum height of 200mm. Automatic water refill guarantees constant heating performances and prevent unit breakage. Electronic overheating protection. Digital control with temperature display with precise adjustment (0,1°C). Fully compliant HACCP digital controls include visible alarms. Designed to work with both hot and cold inlet water. Etched foil heating elements to maximize heat transmission for reduced warm-up times. Well in 304 AISI stainless steel with rounded corners to facilitate cleaning operations. The well is also equipped with a drain hole. Well bottom is inclined to guarantee full well drainage. 19mm thick glass wool isolated with galvanize sheet guarantees excellent well insulation to reduce energy dispersion. Heating elements connected to the well bottom include safety thermostat. Food introduced at the correct temperature maintains its core temperature according to Afnor Standards.

Main Features

- Electronic overheating protection.
- Designed to serve the food in gastronorm containers.
- Suitable for GN 1/1 containers with a maximum height of 200 mm.
- Automatic water refill guarantees constant heating performances and prevent unit breakage.
- Precise temperature control and setting at 0,1°C .
- As standard the product comes with digitally controlled thermostat which is in line of HACCP norms and provides visual alarm as a warning of the increasing or decreasing temperatures.
- Designed to work with both hot and cold inlet water.
- Etched foil heating elements to maximize heat transmission for reduced warm-up times.
- It is possible to transform one of the GNs to soup dispenser with the available accessory.
- CB and CE certified by a third party notified body.
- Designed to be positioned in flush installation providing improved cleanability and suitable for modern design installations.
- Available drop-in dimensions: 2, 3, 4, 5, 6 GN.
- Food introduced at the correct temperature maintains its core temperature according to Afnor Standards.

Construction

- Heating elements connected to the well bottom include safety thermostat.
- Well bottom is inclined to facilitate water drainage.
- IPx4 water protection.
- Well in 304 AISI stainless steel with rounded corners to facilitate cleaning operations. The well is also equipped with a drain hole.
- Electronic control with temperature display.
- 19mm thick rock wool isolated with galvanize sheet guarantees excellent well insulation to reduce energy dispersion.


APPROVAL: _____




Electrolux
PROFESSIONAL

Drop-In Drop-in bain-marie, with one well (3 GN container capacity)

Side



Top



D = Drain
EI = Electrical inlet (power)
WI = Water inlet

Electric

Supply voltage:

341001 (D01H3)

220-240 V/1N ph/50/60 Hz

Electrical power max.:

2.02 kW

Water:

Water inlet "CW" connection: 1/2"

Drain line size: 1"

Key Information:

External dimensions, Width: 1100 mm

External dimensions, Height: 260 mm

External dimensions, Depth: 620 mm

Net weight: 28.3 kg

Shipping weight: 42.7 kg

Shipping height: 380 mm

Shipping width: 1140 mm

Shipping depth: 660 mm

Shipping volume: 0.29 m³

Set temperature: +85 / +95 °C




Noise level: 0 dBA





Drop-In
Drop-in bain-marie, with one well (3 GN container capacity)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2020.11.12



	J1	A1	Y1	Z1
2 GN	700	880	80	20
3 GN	1030	1200		
4 GN	1350	1530		
5 GN	1670	1850		
6 GN	2000	2180		



3. IDS WATER BAIN MARIE SINGLE WELL