

Refrigerated



Contact cooled Island - CARIB1.3

CARIB1.3

Designed to achieve a deck temperature of 0°C to 1°C in temperatures not exceeding 32°C

cooled well models. Model No: CARIB1.312 - 1206mm long Model No: CARIB1.316 - 1606mm long Model No: CARIB1.319 - 1906mm long
shows CARIB1.319 finished in beech effect plastic coated steel long unit with the optional extras of Caribbean Island gantry. GANDB19F

Contact

Picture

Specifications

Dimensions: Model ----- Dimensions ----- loading CARIB1.312 --- 1206 x 700 x 900mm high --- 1.5kW CARIB1.316 --- 1606 x 700 x 900mm high --- 1.5kW CARIB1.319 --- 1906 x 700 x 900mm

high --- 1.5kW **Refrigerant:** R404 CFC free refrigerant

0°C to + 1°C up to maximum ambient of +32°C RH 60

loading 6.3Amps approx Cable: 2 metres with 13 amp plug fitted

Exterior: Colour plastic coated steel or Stainless steel. Well: Stainless Steel.

Capacity 1206 model - 1010 x 580 x 100mm - 3 x GN1/1 x 100mm deep 1606 model - 1310 x 580 x 100mm - 4 x GN1/1 x 100mm deep 1906 model - 1610 x 580 x 100mm - 5 x GN1/1 x 100mm deep

Operating Conditions:

Electrical Connection

Construction

Well Base temperature 220V/240V 1 phase 50Hz 1.5kW

Top: Stainless Steel

Well Dimensions &

Features

Standard Features:

- Slide out refrigeration modules for ease of maintenance.
- One piece 304 grade stainless steel well radiused to base for ease of cleaning.
- Automatic defrost & condense handling system.
- 1.5mm stainless steel tops with radius front & rear.
- Four x 100mm swivel castors two braked.
- 14 different colour coated steel finish options.

Extras:

- Alternative Gantries & overshelves
- Tray rails.
- Corner bumpers
- Push bar
- Height adjustable feet instead of castors

Victor Manufacturing Limited

Lonsdale Works, Gibson Street, Bradford, BD3 9TF, West Yorkshire, England
Tel: +44 (0)1274 722125 Email: email@victormanufacturing.co.uk
Copyright © 2014 Victor Manufacturing Limited