



UTENSIL WASHER LU-60B 230-400/50/3N (WITH DRAIN PUMP)

600 x 630 mm. basket

1300574



WARE WASHING
POT WASHERS

SALES DESCRIPTION

Max. loading height: 650mm.

FEATURES AND BENEFITS

Ideal to wash big sized pots and wares.

- ✓ Powerful and high pressure: specially indicated for restaurants, ice-cream shops, pastries and butcheries.
- ✓ Constructed from stainless steel.
- ✓ Door divided in two parts, perfectly counterbalanced, easy to handle.
- ✓ Double skinned machines: silent working and reduced thermal dispersions.
- ✓ Wash tank without corners to avoid dirt accumulation in angles.
- ✓ Stamped wash dispersers in stainless steel tubes.
- ✓ Easy to remove wash- and rinse dispersers.
- ✓ Safety micro switch at the door and electronic safety device to guarantee washing temperature and time.
- ✓ Electronic control panel with LED showing wash and rinse temperature.

INCLUDES

- ✓ 1 stainless steel basket and insert for 4 trays.

ACCESSORIES

- Stainless steel baskets
- Manual water softeners
- Automatic water softeners
- Dosing equipments
- Carrier for trays



www.sammic.co.uk
 Food Service Equipment Manufacturer
 Unit 2, Trevanah Road
 Troon Industrial Park
 LE4 9LS - Leicester
 uksales@sammic.com
 Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	

product sheet
updated 27/03/2020



UTENSIL WASHER LU-60B 230-400/50/3N (WITH DRAIN PUMP)

600 x 630 mm. basket

1300574

SPECIFICATIONS

Basket dimensions: 600 mm x 630 mm
 Stainless steel basket : 1
 Equipment: supplementary trays: 1
 Maximum glass height: 650 mm
 Cycles: 3
 Cycle duration: 120 " / 240 " / 360 "
 Production baskets/hour: 30 / 15 / 10
 Pressure pump power: 470 W
 Electrical supply: 230 V - 400 V / 50 Hz / 3N
 ~ (30.4 A-17 A)

Loading



- ✓ Pump: 3 Hp / 2200 W
- ✓ Tank: 6000 W
- ✓ Boiler: 9000 W
- ✓ Total loading: 11200 W
- Feed water temperature: 10 °C - 60 °C
- Wash temperature: 40 °C - 70 °C
- Rinse temperature: 70 °C - 95 °C
- Wash tank capacity: 60 l
- Boiler capacity: 12 l
- Water consumption/cycle: 5 l
- Drainage base maximum height: 185 mm
- Drain diameter: 30 mm

External dimensions (WxDxH)

- ✓ Width: 742 mm
- ✓ Depth (closed): 852 mm
- ✓ Depth (open): 1232 mm
- ✓ Height (closed): 1840 mm
- ✓ Height (open): 2035 mm
- Net weight: 168 Kg
- Noise level (1m.): 76 dB(A)

Crated dimensions

790 x 980 x 1950 mm
 Gross weight: 181 Kg.



A- Entrada de agua 3/4" GAS
 B- Tubo de desague Ø30 mm

WARE WASHING
POT WASHERS



www.sammic.co.uk
 Food Service Equipment Manufacturer
 Unit 2, Trevanah Road
 Troon Industrial Park
 LE4 9LS - Leicester
 uksales@sammic.com
 Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	

product sheet
updated 27/03/2020