



# Induced Energy

## CS3000KH-P Induction Keep Hot Unit

Model CS3000KH (Ceran) or CS3000KH-P (Invisible).- Induction keep hot. Suitable for drop-in with ceran top or through selected stone types.



### Product Specifications

|                          |   |
|--------------------------|---|
| <b>Maximum Power</b>     | 0.8kW   |
| <b>Electrical Supply</b> | 230V AC 50Hz (50-60 Hz version also available) 13 amp single phase supply                                     |
| <b>Cord &amp; Plug</b>   | Cord length 1.8m<br>Moulded 13-amp plug fitted (UK)<br>Appropriate plug for each export market                |
| <b>Weight</b>            | 9.5kg   |
| <b>Dimensions (mm)</b>   | Drop-in case: 395 x 395 x 140mm<br>Front control panel: 350 x 90mm (Optional)<br>Ceran footprint: 400 x 400mm |
| <b>Depth of Field</b>    | Up to 30mm  |
| <b>Safety Features</b>   | Pan detection; boil-dry protection; overheat prevention; clean filter warning                                 |
| <b>User Interface</b>    | Display panel: Clean filter warning; No Pan Present warning; Glass/Lava hot warning; Shutdown                 |
| <b>Controls</b>          | Ergonomically designed knob with precise settings of 1 to 25  |
| <b>Bespoke Options</b>   | Overall design/size, Lava options, natural or coloured glazed   |
| <b>Warranty</b>          | 2 years parts and labour, excluding lava stone top  |
| <b>CE</b>                | Approved  |
| <b>Stone</b>             | Maximum thickness of stone is 15mm. Lava stone is recommended   |

*Induced Energy Ltd. Operate a continuous programme of product development and improvement. Product specifications may therefore be subject to change.*

Induced Energy Ltd, Westminster Road, Brackley, Northants NN13 7EB  
Tel: 01280 875400 Email: sales@inducedenergy.com