

# WOK 2 BURNER GAS 14KW ON OPEN COMPARTMENT

Project: .....  
Rev.: .....  
Zone: .....  
Location: .....



CODICE  
CR0991809

MODELLO  
D95/10CGW28

SERIE  
DIAMANTE90



## GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200. Wide range of accessories.

## TECHNICAL SPECIFICATIONS

Table tops with 20/10 thickness with 55x52 cm or 95x52 cm storage space.  
Right rear exhaust 22 mm in diameter, prepared for ground connection.  
In the compartment area, full-width tray for collecting overflow liquids.

Enamelled cast iron ring burner, available in 10 or 14 kW, removable for easier cleaning.

Table top with standardised tank and liquid drainage in the rear right-hand corner.

Tray for collecting overflow liquids.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

# WOK 2 BURNER GAS 14KW ON OPEN COMPARTMENT

Project: .....  
Rev: .....  
Zone: .....  
Location: .....



CODICE  
CR0991809

MODELLO  
D95/10CGW28

SERIE  
DIAMANTE90

## Technical Information

SPECIFICATION	DATA
MATERIAL	CR0991809
DEFINITION	D95/10CGW28 2 FUOC. WOK 28KW COMPARTMENT
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	860 mm
DIM. PRODUCTIVITY	1020 mm
DIM. HEIGHT	870 mm
NET WEIGHT	115 Kg
VOLUME (net)	0,763
PACKAGE LENGTH	1250,000 mm
PACKAGE WIDTH	1020,000 mm
PACKAGING HEIGHT	1150,000 mm
PACKAGE VOLUME	1,462 m3
GROSS PACKING WEIGHT	131,600 Kg
GAS POWER	28,00
GAS POWER (G25.3/25mbar)	26,60
GAS/REFRIGERANT TYPE	GPL 28-30/37 mbar
N. FIRES/PLATES	QUATTRO FUOCHI
CERTIFIED MODEL	D95/10 CGW

# WOK 2 BURNER GAS 14KW ON OPEN COMPARTMENT

Project: .....  
 Rev: .....  
 Zone: .....  
 Location: .....




CODICE  
CR0991809

MODELLO  
D95/10CGW28

SERIE  
DIAMANTE90

## SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR

MISURE IN mm - DIMENSIONS IN mm - ABMESSUNGEN IN mm  
 MESURES EN mm - MEDIDAS EN mm - MATEN IN mm



### Legenda - Legende - Key - Légende - Leyenda - Legenda

- G** Attacco arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting **EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)**
- S** Scarico acqua - Wasserablauf - Water drain - Evacuation eau - Descarga de agua - Afvoer water **EN 10226-1 R 1**

# WOK 2 BURNER GAS 14KW ON OPEN COMPARTMENT

Project: .....  
Rev: .....  
Zone: .....  
Location: .....



CODICE  
CR0991809

MODELLO  
D95/10CGW28

SERIE  
DIAMANTE90

## Product's PLUS



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.



Enamelled cast iron ring burner, available in 10 or 14 kW, removable for easier cleaning.



Table top with standardised tank and liquid drainage in the rear right-hand corner.



Tray for collecting overflow liquids.

# WOK 2 BURNER GAS 14KW ON OPEN COMPARTMENT

Project: .....  
Rev: .....  
Zone: .....  
Location: .....



CODICE  
CR0991809

MODELLO  
D95/10CGW28

SERIE  
DIAMANTE90

## ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR0996989	DBVP5	
CR0592820	9ZL	
MA97432000	R	
MA97433000	RI	
CR0592869	PZM	
CR0593580	9PT	
CR0592879	KPA	
CR0592940	9CAT *	Water column for top equipment