Model:

Underbar Refrigeration:

SDD-27-58

27" Direct Draw Beer Dispenser





SDD-27-58

CABINET CONSTRUCTION Standard, cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish. Stainless exterior options available. Standard interior construction utilizes stainless steel walls, floor and ceiling. REFRIGERATION Refrigeration system uses R134a refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns. **ELECTRICAL** Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. **TEMPERATURE** Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C) SANITATION NSF-7 approved for packaged and

bottled product. MODEL FEATURES:

- Standard LED light inside of the cabinet
- Easily accessible condenser coil for cleaning, and easy service access
- Designed to accommodate a variety of beer kegs

General Specification

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

			Cabinet Dimensions (inches / mm)			Capacity				
Model	Doors	Shelves	L	D	Н	1/2 Barrels	HP	Voltage	Amps	NEMA Config.
SDD-27-58	2	4	58 7/8 1495	27 3/4 705	35 5/8 905	2	1/3+	115/60/1	6.2	5-15P

• Height does not include 15 1/4" (388mm) for draft arm.



• Plug type varies by country.

• Height does not includes 3" casters.

• Two-faucets column is option

SDD-27-58 Plan View



