



**S-23RG
S-23FG**



**S-47RG
S-47FG**



**S-72RG
S-72FG**

Door	1	2	3
Shelves	3	6	9
Exterior Dimensions (L x D x H)	29 x 32 ¼ x 82 ½	54 x 32 ¼ x 82 ½	81 x 32 ¼ x 82 ½
Capacity cu.ft.	23	47	72
HP	1/4 3/4	1/2 1-1/4	3/4 1-1/4
Voltage	115/60/1	115/60/1	115/60/1
Amps	7.4 9.6	9.4 14.4	10.4 15
Nema Config	5-15P	5-15P 5-20P 30 amps Circuit Breaker is recommended to be connected to the plug base directly.	5-15P 5-20P 30 amps Circuit Breaker is recommended to be connected to the plug base directly.
Crated/Uncrated Weight	341/282 lb	550/447 lb	704/616 lb

- Bottom mount condensing unit
- Stainless steel interior and exterior
- Glass Door for ease in checking inventory without opening the doors
- Rounded corner design for easy cleaning of inside storage
- Heavy duty pull handle; Each door has two spring hinges making the door self-closing
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) or -8°F to 0°F (-22°C to -18°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- Standard heavy duty casters make it easy to move and clean underneath
- LED lighting: Visibility of products, last longer and consume low energy

* Specifications subject to change without notice

