


SINGLE HOB

INDUCTION COOKTOP

NON-TOUCH DISPLAY



HELIOS STANDARD, COUNTERTOP



HELIOS STANDARD, DROP-IN

TOUCH DISPLAY



HELIOS TOUCH, COUNTERTOP

FEATURES

- 1800 (US and Canada), 2500 and 3500 W models
- Available in 100–120 or 200–240 VAC, single-phase
- Countertop or drop-in design with stainless-steel housing
- Sloped front panel allows for a countertop design
- Helios Standard or Helios Touch display options for countertop design
- High-quality internal electronics and heavy-gauge Litz wire
- Easy-to-clean high-temperature glass-ceramic top
- 4.3-inch display
- Even heat distribution across the bottom of cookware*
- Temperature ranges from 85–425 °F (29–218 °C)
- Automatic pan detection provides instant energy transfer to cookware
- Automatic shut-off feature prohibits overheating
- Integral grease filter and air baffle maintain cooler, cleaner air intake
- Integral fan to keep internal components cool
- Microprocessors continuously monitor vital components for overheating, power-supply issues, and other conditions

STANDARD INCLUDED ACCESSORIES


- Two-year advanced replacement warranty (U.S. and Canada)
- Standard Cat 5e or Cat 6 patch cable from unit to control box
- 6-ft (1.8 m) nominal plug and cord




*Induction cooking requires the use of induction-compatible (i.e., magnetic) cookware.

It is the owner and installer's responsibility to comply with all local codes. CookTek reserves the right to substitute components or change specifications without prior notice.


HELIOS
STANDARD
COUNTERTOP



HELIOS
STANDARD
DROP-IN



HELIOS TOUCH
COUNTERTOP



DIMENSIONS - HELIOS STANDARD COUNTERTOP		
Full Unit Height	4.9"	125 mm
Full Unit Width	13.7"	347 mm
Full Unit Depth	18.5"	470 mm
Feet Height	1.2"	31 mm
Weight	19 lb	8.6 kg
Max Ambient Temperature	122 °F	50 °C
DIMENSIONS - HELIOS STANDARD DROP-IN		
Full Unit Height	3.7"	93 mm
Full Unit Width	13.5"	343 mm
Housing Width	12.8"	324 mm
Full Unit Depth	13.5"	343 mm
Housing Depth	12.8"	324 mm
Cutout Width	13.13"	334 mm
Cutout Depth	13.13"	334 mm
Weight	15 lb	6.8 kg
Max Ambient Temperature	122 °F	50 °C
DIMENSIONS - HELIOS TOUCH COUNTERTOP		
Full Unit Height	4.9"	125 mm
Full Unit Width	13.7"	347 mm
Full Unit Depth	18.5"	470 mm
Feet Height	1.2"	31 mm
Weight	19 lb	8.6 kg
Max Ambient Temperature	122 °F	50 °C

WALL CLEARANCE*		
Front	2"	51 mm
Sides	2"	51 mm
Rear	2"	51 mm

*The clearances provided apply to a unit not placed near a heat source. Refer to the owner's manual for clearance requirements if the unit is placed near a heat source.

SHIPPING INFORMATION		
Packaged Height	9"	229 mm
Packaged Width	18.75"	476 mm
Packaged Depth	20.75"	527 mm
Packaged Weight	24 lb	10.9 kg
Item Class	250 NMFC #26710	

ELECTRICAL SPECIFICATIONS – SINGLE PHASE HELIOS STANDARD COUNTERTOP		
UNITED STATES/CANADA		
HRF-9500-SH18-1	100–120 V, 50/60 Hz, 1800W	NEMA 5-15P
HRF-9500-SH25-1	200–240 V, 50/60 Hz, 2500W	NEMA 6-20P
HRF-9500-SH35-1	200–240 V, 50/60 Hz, 3500W	NEMA 6-20P
UK/MIDDLE EAST		
HRF-9500-SH25-2	200–240 V, 50/60 Hz, 2500W	BS1363, 13A, 230V
HRF-9500-SH35-2	200–240 V, 50/60 Hz, 3500W	IEC 309, 16A, 3-pin
AUSTRALIA		
HRF-9500-SH25-4	200–240 V, 50/60 Hz, 2500W	AS/NZS 3112:2000, 10A, 250V
HRF-9500-SH35-4	200–240 V, 50/60 Hz, 3500W	AS/NZS 3112:2000, 15A, 250V
JAPAN		
HRF-9500-SH25-6	200–240 V, 50/60 Hz, 2500W	NEMA 6-20P
HRF-9500-SH35-6	200–240 V, 50/60 Hz, 3500W	NEMA 6-20P
SOUTH AFRICA		
HRF-9500-SH25-7	200–240 V, 50/60 Hz, 2500W	BS 546, 16A, 250V
HRF-9500-SH35-7	200–240 V, 50/60 Hz, 3500W	BS 546, 16A, 250V
ISRAEL		
HRF-9500-SH25-8	200–240 V, 50/60 Hz, 2500W	SI 32, 16A, 250V
HRF-9500-SH35-8	200–240 V, 50/60 Hz, 3500W	SI 32, 16A, 250V



AS/NZS
3112:2000, 10A,
250V



BS1363, 13A, 230V



NEMA 5-15P



AS/NZS
3112:2000, 15A,
250V



CEE 7/7 Schuko, 16A,
250V



NEMA 6-20P



BS 546, 16A,
250V



IEC 309, 16A, 3-pin



SI 32, 16A,
250V

ELECTRICAL SPECIFICATIONS - SINGLE PHASE HELIOS STANDARD DROP-IN		
UNITED STATES/CANADA		
HRD-9500-SH18-1	100–120V, 50/60 Hz, 1800W	NEMA 5-15P
HRD-9500-SH25-1	200–240 V, 50/60 Hz, 2500W	NEMA 6-20P
HRD-9500-SH35-1	200–240V, 50/60 Hz, 3500W	NEMA 6-20P
UK & SAUDI ARABIA		
HRD-9500-SH25-2	200–240 V, 50/60 Hz, 2500W	BS1363, 13A, 230V
HRD-9500-SH35-2	200–240V, 50/60 Hz, 3500W	IEC 309, 16A, 3-pin
INTERNATIONAL		
HRD-9500-SH25-3	200–240 V, 50/60 Hz, 2500W	CEE 7/7 Schuko, 16A, 250V
HRD-9500-SH35-3	200–240V, 50/60 Hz, 3500W	CEE 7/7 Schuko, 16A, 250V
AUSTRALIA		
HRD-9500-SH25-4	200–240 V, 50/60 Hz, 2500W	AS/NZS 3112:2000, 10A, 250V
HRD-9500-SH35-4	200–240V, 50/60 Hz, 3500W	AS/NZS 3112:2000, 15A, 250V
JAPAN		
HRD-9500-SH25-6	200–240 V, 50/60 Hz, 2500W	NEMA 6-20P
HRD-9500-SH35-6	200–240V, 50/60 Hz, 3500W	NEMA 6-20P
SOUTH AFRICA		
HRD-9500-SH25-7	200–240 V, 50/60 Hz, 2500W	BS 546, 16A, 250V
HRD-9500-SH35-7	200–240V, 50/60 Hz, 3500W	BS 546, 16A, 250V
ISRAEL		
HRD-9500-SH25-8	200–240 V, 50/60 Hz, 2500W	SI 32, 16A, 250V
HRD-9500-SH35-8	200–240V, 50/60 Hz, 3500W	SI 32, 16A, 250V

ELECTRICAL SPECIFICATIONS - SINGLE PHASE HELIOS TOUCH COUNTERTOP		
UNITED STATES/CANADA		
HTF-9500-SH18-1	100–120V, 50/60 Hz, 1800W	NEMA 5-15P
HTF-9500-SH25-1	200–240 V, 50/60 Hz, 2500W	NEMA 6-20P
HTF-9500-SH35-1	200–240V, 50/60 Hz, 3500W	NEMA 6-20P
UK & SAUDI ARABIA		
HTF-9500-SH25-2	200–240V, 50/60 Hz, 2500W	BS1363, 13A, 230V
HTF-9500-SH35-2	200–240V, 50/60 Hz, 3500W	IEC 309, 16A, 3-pin
INTERNATIONAL		
HTF-9500-SH25-3	200–240V, 50/60 Hz, 2500W	CEE 7/7 Schuko 16A, 250V
HTF-9500-SH35-3	200–240V, 50/60 Hz, 3500W	CEE 7/7 Schuko 16A, 250V
AUSTRALIA		
HTF-9500-SH25-4	200–240V, 50/60 Hz, 2500W	AS/NZS 3112:2000, 10A, 250V
HTF-9500-SH35-4	200–240V, 50/60 Hz, 3500W	AS/NZS 3112:2000, 15A, 250V
JAPAN		
HTF-9500-SH25-6	200–240V, 50/60 Hz, 2500W	NEMA 6-20P
HTF-9500-SH35-6	200–240V, 50/60 Hz, 3500W	NEMA 6-20P
SOUTH AFRICA		
HTF-9500-SH25-7	200–240V, 50/60 Hz, 2500W	BS 546, 16A, 250V
HTF-9500-SH35-7	200–240V, 50/60 Hz, 3500W	BS 546, 16A, 250V
ISRAEL		
HTF-9500-SH25-8	200–240V, 50/60 Hz, 2500W	SI 32, 16A, 250V
HTF-9500-SH35-8	200–240V, 50/60 Hz, 3500W	SI 32, 16A, 250V

⚠️ Dedicated circuit required for each installation